


AFIT/GEE/ENV/94S-06

AD-A284 886



A RETROSPECTIVE QUANTITATIVE ASSESSMENT OF  
TRICHLOROETHYLENE EXPOSURE OF WORKERS AT  
AIRCRAFT MAINTENANCE FACILITIES AT HILL AIR  
FORCE BASE THROUGH THE USE OF MODELING

THESIS

Anthony O. Copeland, Captain, USAF

AFIT/GEE/ENV/94S-06

1038  
94-30497



Approved for public release; distribution unlimited

DTIC QUALITY INSPECTED 3

94 9 22 0 4 6

The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.

|               |                                     |
|---------------|-------------------------------------|
| Accession For |                                     |
| NTIS CRA&I    | <input checked="" type="checkbox"/> |
| DTIC TAB      | <input type="checkbox"/>            |
| Unannounced   | <input type="checkbox"/>            |
| Justification |                                     |
| By            |                                     |
| Distribution  |                                     |
| Availability  |                                     |
| Dist          | Availability<br>Special             |
| A-1           |                                     |

AFTT/GEE/ENV/94S-06

A RETROSPECTIVE QUANTITATIVE ASSESSMENT OF TRICHLOROETHYLENE  
EXPOSURE OF WORKERS AT AIRCRAFT MAINTENANCE  
FACILITIES AT HILL AIR FORCE BASE THROUGH  
THE USE OF MODELING

THESIS

Presented to the Faculty of the School of Engineering

of the Air Force Institute of Technology

Air University

In Partial Fulfillment of the

Requirements for the Degree of

Master of Science in Engineering and Environmental Management

Anthony O. Copeland, B.S.

Captain, USAF

September 1994

Approved for public release; distribution unlimited

### *Acknowledgments*

Very special thanks goes to my lovely fiancée, Lisa. Without her support, encouragement, kind ear, and timely sense of humor, completing this project would have been nearly impossible. Thanks also goes to Fred Cade for providing comic relief when the going got rough - I'm going to miss those late night, stupid jokes and the Def Comedy Jam recordings. I'd also like to express my gratitude to Dan Marano, Lt Col Nu, Dr. Klinko, SSgt Fortunato, and the members of the Hill AFB Bio-Environmental Engineering Flight for the valuable assistance they provided during my site visit. Finally, I'd like to thank my advisor, Lt Col Dan Caldwell, for affording me the right mix of freedom and guidance, thus making the entire thesis writing process truly rewarding and memorable.

- Anthony O. Copeland.

## ***Table of Contents***

|                                 | <b>Page</b> |
|---------------------------------|-------------|
| <b>Acknowledgments</b>          | <b>ii</b>   |
| <b>List of Figures</b>          | <b>v</b>    |
| <b>List of Tables</b>           | <b>vii</b>  |
| <b>Abstract</b>                 | <b>ix</b>   |
| <b>I. Introduction</b>          | <b>1</b>    |
| General Issue                   | 1           |
| Specific Problem                | 4           |
| Investigative Questions         | 4           |
| Scope and Limitation            | 5           |
| <b>II. Literature Review</b>    | <b>6</b>    |
| Introduction                    | 6           |
| Background of Trichloroethylene | 6           |
| History                         | 6           |
| Carcinogenicity                 | 8           |
| Exposure Routes                 | 12          |
| Exposure Assessment             | 17          |
| Hill AFB Epidemiology Study     | 17          |
| Estimating Historical Exposures | 21          |
| Exposure Modeling               | 23          |
| <b>III. Methodology</b>         | <b>28</b>   |
| Introduction                    | 28          |
| Objective 1                     | 28          |
| Objective 2                     | 29          |
| Objective 3                     | 29          |
| <b>IV. Analysis and Results</b> | <b>30</b>   |
| Introduction                    | 30          |

|  |        |
|--|--------|
| Feasibility of Reconstructive Modeling | 30     |
| Results                                | 31     |
| Shop Details                           | 31     |
| Monitoring Data                        | 32     |
| Summary                                | 37     |
| Monte Carlo Simulation Analysis        | 37     |
| Background                             | 37     |
| Results                                | 38     |
| Multi-Point Diffusion Model Analysis   | 49     |
| Background                             | 49     |
| Results                                | 50     |
| <br>V. Conclusion                      | <br>61 |
| <br>Appendix A: Tables                 | <br>66 |
| <br>Appendix B: Photographs            | <br>81 |
| <br>Bibliography                       | <br>86 |
| <br>Vita                               | <br>90 |

### ***List of Figures***

| <b>Figure</b>  | <b>Page</b> |
|--|-------------|
| 1. Metabolic Pathways of TCE in Humans and Rodents   | 9           |
| 2. Distribution of Breathing Zone Concentration Data   | 35          |
| 3. Normal Approximation of Breathing Zone Concentration Data   | 39          |
| 4. Difference in Normal Approximation and Breathing Zone Concentration Data  | 39          |
| 5. Weibull Approximation of Breathing Zone Concentration Data  | 40          |
| 6. Difference in Weibull Approximation and Breathing Zone Concentration Data   | 40          |
| 7. Triangle Approximation of Breathing Zone Concentration Data   | 41          |
| 8. Difference in Triangle Approximation and Breathing Zone Concentration Data  | 41          |
| 9. Annual TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Normal Distribution   | 43          |
| 10. Annual TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Histogram Generated by the Breathing Zone Concentration Data     | 43          |
| 11. Cumulative TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Normal Distribution  | 44          |
| 12. Cumulative TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Histogram Generated by the Breathing Zone Concentration Data | 45          |
| 13. TCE Inhalation Intake (mg/kg-day) with Breathing Zone Concentrations Modeled Using the Normal Distribution   | 46          |
| 14. TCE Inhalation Intake (mg/kg-day) with Breathing Zone Concentrations Modeled Using the Histogram Generated from the Breathing Zone Concentration Data              | 46          |

|     |   |    |
|-----|---|----|
| 15. | Cancer Risk with TCE Inhalation Intake (mg/kg-day) Calculated Using the Normal Distribution to Model Breathing Zone Concentrations                            | 47 |
| 16. | Cancer Risk with TCE Inhalation Intake (mg/kg-day) Calculated Using the Histogram of Breathing Zone Concentration Data  | 47 |
| 17. | Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 10 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations | 58 |
| 18. | Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 20 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations | 59 |
| 19. | Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 30 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations | 59 |
| 20. | Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 40 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations | 60 |
| 21. | Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 50 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations | 60 |



### ***List of Tables***

| <b>Table</b>  | <b>Page</b> |
|---|-------------|
| 1. Comparison of Adult Daily Doses of TCE in Tap Water by Dermal, Oral, and Respiratory Route (mg/day)  | 16          |
| 2. Frequency and Duration of Use of TCE and Mixed Solvents  | 20          |
| 3. Indices Used in Exposure Estimation  | 34          |
| 4. TCE Breathing Zone Concentration Levels of Vapor Degreaser Workers   | 33          |
| 5. Descriptive Statistics of Breathing Zone Concentration Data  | 35          |
| 6. Description of Model Parameters  | 42          |
| 7. Summary Statistics for Outputs of Monte Carlo Simulation of Exposure to Degreaser Breathing Zone Concentrations Only   | 48          |
| 8. Two-Point Diffusion Model Parameters   | 50          |
| 9. Eddy Diffusivities and Steady-State Emissions Resulting from Application of the 2-Point Diffusion Model Using the Data in Table 8  | 51          |
| 10. Predicted Concentrations at Various Distances from Degreasing Activities Using the Calculated Eddy Diffusivities and Steady-State Emission Rates Presented in Table 9       | 52          |
| 11. Summary Statistics for Simulation of TCE Intake at Various Distances Resulting From Background Concentration Levels Only  | 54          |
| 12. Summary Statistics for Simulation of Total TCE Intake at Various Distances Resulting From Both Background and Degreaser Breathing Zone Concentration Levels                 | 55          |
| 13. Summary Statistics for Simulation of Annual TWA Exposure Due to Exposure to Both Background Concentrations at Various Distances and Degreaser Breathing Zone Concentrations | 56          |

|     |   |           |
|-----|---|-----------|
| 14. | <b>Summary Statistics for Simulation of Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at Various Distances and Degreaser Breathing Zone Concentrations</b> | <b>57</b> |
|-----|---|-----------|

### *Abstract*

Monte Carlo simulation and source-receptor modeling are used to estimate the TCE exposures encountered by select workers at aircraft maintenance facilities at Hill Air Force Base between 1955 and 1979. An epidemiological study of this group, a retrospective cohort study of 14,457 workers who were employed at the base for a minimum of one year between 1952 and 1956, was headed by Dr. R. Spirtas of the National Cancer Institute to evaluate mortality associated with occupational exposure. One of the major conclusions of the study was that TCE "probably does not pose a strong carcinogenic risk for man." In the Spirtas study, historic exposure levels were not quantitatively estimated. Instead, indices of exposure to TCE were assigned to reflect relative differences in exposure levels. It is the objective of this research effort to quantitatively estimate specific worker exposures, thus adding to the weight of evidence necessary to classify TCE as a human carcinogen or otherwise.

**A RETROSPECTIVE QUANTITATIVE ASSESSMENT OF  
TRICHLOROETHYLENE EXPOSURE OF WORKERS AT AIRCRAFT  
MAINTENANCE FACILITIES AT HILL AIR FORCE BASE THROUGH THE  
USE OF MODELING**

***I. Introduction***

This chapter provides background information on the general issue of trichloroethylene (TCE) contamination of soil and groundwater found at military installations across the country. The importance from both a financial and human health standpoint are briefly discussed. Finally, discussed in this chapter are the specific problem, investigative questions, and the scope and limitations of this research.

***General Issue***

Trichloroethylene exists as a clear, colorless, nonflammable, volatile liquid and is primarily used as a dry-cleaning solvent or a degreasing agent (Manahan, 1990:76). The Department of Defense (DoD), in the past, used TCE primarily as an industrial solvent. Usage, storage, and disposal practices of the past have resurfaced as soil and groundwater contamination problems today. The majority of all DoD installations found on the National Priorities List (NPL) are in some manner contaminated with chlorinated organic liquids, with TCE being among the most common. In several cases the contamination has affected groundwater sources found on the installations.

Additionally, migration off-site has occurred and affects public and private water supplies in some areas. Incidents of solvent contamination of soils and groundwater are not confined to DoD installations. Private industry has experienced similar usage and disposal practices as military installations and subsequently is responsible for sites in which TCE and other halogenated hydrocarbons have contaminated soil and groundwater.

It has been suggested by John Cherry, a leading consultant on problems of groundwater contamination, that chlorinated organic solvents are by far the most prevalent sources of industrial groundwater contamination. He has also noted that we do not presently have the technological capability to remediate an aquifer to current drinking water standards if that aquifer is contaminated with a free or residual phase of an immiscible contaminant, such as chlorinated organic liquids (Bredehoett, 1992:834). The DoD and the United States Environmental Protection Agency (USEPA) have declared TCE a priority groundwater contaminant; the USAF has made TCE its number one chemical of concern (Fisher, 1993:2).

The magnitude of the TCE contamination problem, both in site size and numbers, coupled with the present maximum contaminant level (MCL) standard for TCE of 5 parts per billion (ppb) presents the DoD a situation in which cleanup costs associated with these sites are enormous. Add to this the fact that it is not always possible to remediate to this level, and the seriousness of TCE contaminated groundwater and its remediation become obvious. The current MCL standard used to determine the level of cleanup taking place on sites today was promulgated in 1987. The basis for the

standard was toxicological data that was current at that time (Fisher, 1993:3). Since the initial establishment of the MCL, the understanding of the mechanisms of action of TCE in rodents and the effects of human exposures have been furthered through additional toxicological and epidemiological data. However, the MCL has remained the same while the current policy guidelines on TCE are under review (Fisher, 1993:3).

Presently, there is an ongoing joint venture (Strategic Environmental Research and Development Program for the Scientific Advisory Board (SERDP SAB); Thrust: Installation Restoration (IR-27), Title: Toxicology and Human Health Risks) between the USEPA, US Army, US Air Force, and the US Navy. The goal of this project is to "conduct specific research studies and incorporate recent research findings on TCE and PCE [perchloroethylene] to support the development of biologically-based health risk standards for TCE and PCE in drinking water and air" (Fisher, 1993:4).

Accomplishment of this objective would result in a current MCL for TCE which would be representative of the actual risks associated with exposure to TCE today. If the revised MCL turned out to be higher than present, this would translate into more cost-effective cleanups of TCE contaminated sites throughout the country for the US government and the private sector because of the less stringent remediation standard. The information necessary to make such a decision will be supported by both toxicological data resulting from the development of a TCE biologically-based model and epidemiological data from recent cohort studies. The purpose of this research is to contribute data to the body of evidence provided by epidemiological data and findings.

### ***Specific Problem***

The specific focus of this research will be to reconstruct, through source-receptor modeling, the TCE exposures encountered by selected workers at aircraft maintenance facilities at Hill Air Force Base between 1954 and 1978. The epidemiological study of this group, a retrospective cohort study of 14,457 workers who were employed at the base for a minimum of one year between 1952 and 1956 and herein referred to as the study, was undertaken by Spirtas et al. to evaluate mortality associated with occupational exposure. One of the major conclusions of the study was that TCE "probably does not pose a strong carcinogenic risk for man" (Spirtas, 1991:528). In the study, the development of historic exposure levels is based on information obtained from facility walk throughs, employee interviews, limited monitoring data, position descriptions, and work practices. It is the objective of this research effort to further refine the exposure estimates of Spirtas et al., thus adding to the weight of evidence necessary to classify TCE as not a human carcinogen.

### ***Investigative Questions***

The investigative questions of this research are as follows:

1. Does sufficient information exist to model historical exposures found in the Hill AFB epidemiology study performed by Spirtas et al?
2. What type of model will best estimate this exposure?
3. What quantitative exposure levels result from applying such a model?

### ***Scope and Limitation***

The study by Spirtas et al. encompassed 14,457 workers who worked under 43,000 unique job titles (Stewart, 1991:531). The difficulty in trying to assimilate occupational and exposure information on each of these jobs from over 40 years ago is the limiting factor with regard to the scope of this research. Evaluation of exposure will be limited to attempting to reconstruct or estimate exposures of workers for which the most information is available . The limitations of this research are determined by the available data describing the work activities found in the areas of interest and the fact that exposure levels will be assessed based on area of work, not specific individual exposures.



## ***II. Literature Review***

### ***Introduction***

The primary purpose of this literature review is two-fold. The first is to equip the reader with a fundamental understanding of the important characteristics of trichloroethylene and provide a perspective of the relative relationship between existing information regarding the health effects of TCE and the current regulatory requirements. A review of the history of TCE, its carcinogenicity, and exposure routes is presented. The secondary purpose is to familiarize the reader with the exposure estimation portion of the epidemiology study that this work is concerned with reconstructing. Additionally, methods for determining a historical occupational exposure history will be discussed.

### ***Background of Trichloroethylene***


A discussion of the history of TCE, its carcinogenicity, and potential exposure pathways is now presented.

***History.*** TCE was first produced in 1864 by Fisher (Feldman, 1970:599). Following that time, it has been produced in Austria and the United Kingdom beginning in 1908, in Germany since 1910, in Japan since 1935, and in the United States since 1925 (Royal Society of Chemistry, 1986:102). TCE, an unsaturated chlorinated hydrocarbon, exists as a dense non-aqueous phase liquid at room temperature. In its liquid state, it is characterized by its clear, colorless appearance, sweet burning taste,

and a pleasant, sweetish odor very similar to that of chloroform (Royal Society of Chemistry, 1986:106). No sources of naturally occurring TCE of any form are known to exist (Royal Society of Chemistry, 1986:102). Primary uses of TCE have been in clinical medicine and industrial processes. The use of TCE for medicinal purposes gained recognition beginning in 1942 when Langston Hewer presented to the Royal Society of Medicine, a report detailing the particulars of the chemistry of TCE, its physical properties, and its potential as an anesthetic (Enderby, 1944:300). Prior to Hewer's presentation, others in the medical field were discovering the effects of TCE on various parts of the central nervous system. Oljenick, in 1928, described, in a report to the Boston Society of Psychiatry and Neurology, the "narcotic" effect of TCE. Three years later, Glaser revealed that TCE depressed the cortex affecting painful stimuli and therefore, could induce anesthesia (Feldman, 1979:458). Because of the known and reported trigeminal neuropathy associated with TCE intoxication and its associated analgesic properties, medical professionals sought its use as a therapy for the treatment of trigeminal neuralgia (*tic douloureux*) and as an inhalant-analgesic-anesthetic for brief operations and various dental and obstetrical procedures (Feldman et al., 1992:490). Presently, due to restrictions regarding its potential health effects, TCE is not used as a general anesthetic or as an analgesic. Additionally, these same restrictions have led to its discontinuance in its application in fumigant mixtures and as an extractant in the decaffeination of coffee (Royal Society of Chemistry, 1986:102). Today, the major use of TCE is in industrial metal cleaning applications. Other uses are found in the electronics industry, in dry-cleaning and textile treatment processes, and the

manufacture of paints, enamels, lacquers, and adhesives (Feldman et al., 1985:119). Additionally, TCE serves as a chain terminator in the production of polyvinyl chloride and is also used as a fire retardant and an extinguisher (Royal Society of Chemistry, 1986:102).

**Carcinogenicity.** In rodents, TCE and its metabolites have been found to be carcinogenic (Allen, 1993:71). As a result of this finding, the EPA currently classifies TCE as a B2 or probable human carcinogen (Cronin, 1993:2-4). The metabolites, trichloroacetic acid (TCA) and dichloroacetic acid (DCA), have been shown to be capable of producing hepatocarcinogenesis in B6C3F1 mice when administered through drinking water (Larson, 1992:278). This same result has been produced when the mice were exposed through inhalation and via gavage. Other rodents, specifically rats, exposed via gavage have developed renal tumors (Allen, 1993:72). These results and those of several other studies suggest that the mechanism of carcinogenicity of TCE is manifested in its metabolites TCA, DCA, and chloral hydrate (Steinberg, 1993:137). Selected steps in the process through which TCE is metabolized in rodents and humans is shown in Figure 1. Although TCE is primarily metabolized in the liver by cytochrome P450 in both rodents and humans, the extent to which the metabolites TCA and DCA are formed varies between the species. In both species the first metabolite formed is trichloroethylene epoxide which then quickly breaks down to form trichloroacetaldehyde and dichloroacetyl chloride. The trichloroacetaldehyde is then hydrated yielding chloral hydrate. The singular chlorine atom of the dichloroacetaldehyde is replaced with a hydroxyl radical, thus forming dichloroacetic



**Figure 1. Metabolic Pathways of TCE in Humans and Rodents (Major metabolic pathways are shown using broad arrows, whereas minor pathways are shown with thin arrows. In rodents, 1,2 dichlorovinyl mercaptan is formed with a reactive thiol group.) (Steinberg, 1993:138).**

acid. This reaction occurs more frequently in rodents than humans. The dichloroacetic acid is further broken down through enzymatic reactions which ultimately lead to

cellular necrosis. Whether chloral hydrate has entered the body as a distinct compound or whether it is formed as described above, once in the body it is quickly metabolized to trichloroethanol and TCA. In humans, TCA is the major toxic metabolite resulting from metabolism of chloral hydrate or TCE. Both trichloroethanol and TCA are further metabolized resulting in the formation of various acids and alcohols. Rodents, mice particularly, metabolize TCE to a greater extent than do humans (Steinberg, 1993:140).

Although no human epidemiological data exists showing increased occurrences of mortalities or malignancies resulting from chronic exposure to TCE, current regulatory guidance is based on a simple linear extrapolation from effects observed in rodents to expected risks in humans. However, the extrapolation is based on the assumption that the low dosages experienced by humans will have the same carcinogenic effect as the high doses which are given to rodents (Steinberg, 1993:137). The underlying assumption on which this linear extrapolation is based centers on TCE and its metabolites having a non-threshold effect - that is to say that any amount of TCE will result in some risk. The accuracy of this assumption is called into question by the fact that the mechanism of carcinogenesis for TCE and its metabolites in rodents is nonlinear. In the lab, large daily doses of TCE (on the order of 1000 mg/kg/day) are administered to rodents to produce cellular necrosis. Once necrosis occurs, a cyclic pattern of regeneration of the effected cells followed by additional necrosis eventually results in malignancy due to the onset of hyperplasia and then neoplasia (Steinberg, 1993:137). Steinberg and DeSesso also note that the aforementioned sequence of events occurs when high doses of chloral hydrate, the precursor to TCA, are

administered, thus further supporting the assumption that TCA and DCA mediate any carcinogenic effects. Hence, considering that TCE itself is not genotoxic and minimally mutagenic, the conclusion can be drawn that in rodents metabolism of TCE is required to produce carcinogenic effects (Steinberg, 1993:141). The relevance of this evidence is that chloral hydrate, the major metabolite of TCE, is also a widely used drug found in sleeping medications and hypnotic sedatives (Cronin, 1993:2-4). Furthermore, levels of TCA and DCA found in drinking water as by-products of the chlorination process are far in excess of those which would result from the metabolism of concentrations of TCE at the current regulatory maximum contaminant level for potable water of 5 ppb (Steinberg, 1993:137). Thus, the metabolites TCA, DCA, and chloral hydrate lead a dichotomous regulatory existence. When produced as a result of metabolism of TCE, they are considered toxic and the parent compound is regulated to the degree that its concentration in potable water shall not exceed 5 ppb. However, when used for medicinal purposes, chloral hydrate, which when metabolized yields TCA, is not subject to stringent regulatory stipulations as is TCE.

The chloracetic acids, TCA and DCA, have recommended safe levels of 175 ppb and 420 ppb respectively when occurring in drinking water as a result of the chlorination process (Steinberg, 1993:145). It is obvious that the likelihood of intaking TCA and DCA is greater if their origin is from the chlorination process, as opposed to the intake and subsequent metabolism of TCE contaminated water at concentrations in the range of 5 ppb. Because of this result and the lack of existence of any epidemiological data supporting TCE as a human carcinogen, Steinberg and DeSesso

suggest that it is possible to increase the allowable level of trichloroethylene in drinking water. They suggest that the current MCL of 5 ppb could be increased to 50 ppb without any increased health risks. Actions by Canadian health and welfare regulatory officials suggest they view the situation in a similar manner, as the recently promulgated TCE drinking water standard in Canada is 50 ppb (Steinberg, 1993:147).

***Exposure Routes.*** Over the past several years, TCE has received much attention due to the fact that it was discovered in many drinking water supplies throughout the country (Wilkes, 1992:2227). The costs associated with remediating these many sites and the concerns of the potentially exposed public have made it a highly controversial contaminant. Within the Air Force, several installations (McClellan AFB, Wright-Patterson AFB, Hill AFB, Castle AFB, etc.) have had to deal with problems of TCE contaminated ground water affecting on-base and off-base water supplies. In cases where the incoming residential water supply was discovered to be contaminated with TCE at levels greater than the established health-based action level, bottled water was provided to the residents for drinking and cooking to minimize exposure through ingestion (Rao, 1993:37). However, because no such action levels exist for bathing, showering, laundry or dishwashing usage, the question arises whether it is safe to perform these activities using the contaminated water (Rao, 1993:37). Beginning in the early eighties and continuing until now, Andelman, McKone, Giardino, Hattis, and others have investigated the routes of exposure associated with residential usage of water contaminated with volatile organic chemicals (VOCs), particularly TCE. Because this route of exposure affects non-volunteer residential subjects and provides

useful information concerning bodily uptake of TCE, it along with occupational exposure routes will be discussed.

Trichloroethylene occurs throughout the environment. It has been found in surface waters, marine life, drinking water supplies, the atmosphere, food, plants, and animal tissues (Callahan et al., 1979:673). In the United States, it is estimated that 80-95% of all TCE produced eventually volatilizes into the atmosphere (Royal Society of Chemistry, 1986:96). Because of its high vapor pressure and Henry's Law Constant, most surface spills and accidental releases of TCE to soil evaporate rapidly. When TCE does leach into ground water, it does so rapidly because of its low adsorption coefficient in a variety of soils (Howard, 1990:468-469). In soil and sediments as well as ground water, it will slowly biodegrade. Ambient concentrations in industrial areas within the United States average 1.2 ppb (Howard, 1990:468-469). Because TCE is ubiquitous throughout the environment, Howard estimates the average daily intake through inhalation to be 0.011-0.033 mg and 0.002-0.020 mg as a result of uptake from ingestion of water.

Historically, quantifying exposure resulting from water ingestion has been viewed as the primary means of assessing exposure from contaminated water sources in residential settings. However, recently it has been found that inhalation of TCE as a result of volatilization from domestic water usage contributes substantially to the total amount of TCE intake. Though several factors such as activity patterns, water-use patterns, and location within the house affect the occupants' inhalation exposure, in cases where the occupant spends a majority of his time at home, inhalation exposure is



likely to equal or exceed exposure resulting from ingestion of the same water (Wilkes, 1992:2227). Experiments by McKone suggest that inhalation exposure derived from showering is equivalent to ingesting 1 to 4 liters of the water. Interestingly, for TCE and other volatile compounds, the transfer efficiency of the compound from the water to air is limited by liquid-phase mass transfer and not gas-phase mass transfer (McKone, 1991:282). This implies that water temperature has little effect on transfer efficiency. Several models including INDOOR, CONTAM, PAQM, and MAVRIQ are available for evaluating various aspects of indoor air quality. MAVRIQ combines various aspects of the aforementioned models to produce a model ideally suited for evaluating exposure resulting from volatilization from water-use activities. Occupant characteristics such as breathing rate, location within the house, activity patterns, water-use activity patterns, air flow patterns and rates, and chemical characteristics are input into the model which then calculates the integrated inhalation exposure of each specified occupant within the home (Wilkes, 1992:2228-2229). The model has been validated several times for theoretical and realistic accuracy. Most recently the model performed very well when applied to an actual case study of a community of several homes where the water supply was contaminated with TCE (Wilkes, 1992:2229).

Another route of exposure which also recently gained recognition as a viable and possible significant exposure pathway in residential exposures is dermal contact with contaminated water. Attempts to model the exposure resulting from dermal contact with contaminated water such as from bathing in contaminated water are presently not as developed and accurate as inhalation modeling. However, this route of exposure

could possibly be as significant as the oral ingestion and inhalation routes of exposure (Brown, 1989:848). The manner in which a chemical enters the body through the skin and the compartmental representation scheme used to model this phenomenon is described by Brown and Hattis below:

We identify two relatively uniform, if not homogeneous, layers of skin: stratum corneum and "skin." The outermost stratum corneum, on the average is approximately 40 micrometers thick, is made up of densely packed keratinized cells and presents the greatest resistance to the movement of molecules across human skin. Organic molecules in dilute aqueous solutions diffuse across the stratum corneum by purely passive means, driven by the concentration gradient between the outer reservoir and the inner layer of skin. Because of the resistance of stratum corneum to the penetrant molecules, the passage across this barrier is the rate-determining step in dermal absorption of chemicals. The stratum corneum behaves as a solution phase of high viscosity and the penetrant must dissolve in it in its passage into the body; thus the rate of transport across stratum corneum depends on the penetrant's solubility in that membrane (stratum corneum/water partition coefficient). ...The compartment labeled skin consists of the viable epidermal layer, the papillary dermis, and possibly inner parts of dermis that may serve as a storage depot for lipophilic chemicals...Chemicals entering the "skin" layer are presumed to diffuse rapidly through the approximate distance of 200 [micrometers] (0.02 cm) between the stratum corneum and blood vessels, diffuse through the capillary walls, and be carried away from "skin" into the blood stream...No distinction is made between a chemical in the dermal blood vessels and a chemical in general circulation. The rate of transfer of a chemical from "skin" into blood is proportional to the instantaneous amount in the "skin," the perfusion rate of the "skin" with blood, and the relative solubilities of the agent in the two compartments (blood/skin partition coefficient). The net rate of change in the amount of chemical in the "skin" depends on the rate of entry from stratum corneum, the rate of removal into blood, and the rate of reentry from the blood (Hattis, 1989:840-841).

Estimating and predicting dermal absorption of a chemical using this approach should be done cautiously, for experimental data to further refine and validate the model is needed. Nonetheless, the model is physiologically representative of the actual process and has very useful applications when used to estimate relative amounts of chemical

absorbed by different individuals under several unique circumstances. Table 1 below shows the range of the predicted daily intake of TCE obtained from taking a 20 minute bath with 73% of the body immersed in water. These values are presented in conjunction with ingestion and inhalation exposures for comparison.

**Table 1. Comparison of Adult Daily Doses of TCE in Tap Water by Dermal, Oral, and Respiratory Routes (mg/day) (Brown and Hattis, 1989:848).**

| Compound           | Concentration (mg/L) | Oral | Respiratory | Minimum Dermal | Maximum Dermal |
|--------------------|----------------------|------|-------------|----------------|----------------|
| Trichloro-ethylene | 0.01                 | 0.02 | 0.0287      | 0.0006         | 0.0096         |
|                    | 0.1                  | 0.2  | 0.287       | 0.006          | 0.096          |

NIOSH estimates that close to 400,000 workers in the United States are exposed to trichloroethylene. Concentrations range anywhere from ten to the hundred parts per million on a continuous basis (Howard, 1990:472). The primary exposure route is inhalation. Adsorption of TCE in its liquid phase through the skin occurs and can be a significant means of exposure if the duration and area of exposure is sufficient. Uptake as a result of adsorption of TCE vapor through the skin is negligible (Royal Society of Chemistry, 1986:114). Thus, the majority of occupational exposure results from inhalation of TCE vapors. Studies of workers who have been chronically exposed to TCE for several years show increased occurrences of various physical ailments (reddening of skin, fatigue, vertigo, headache, bradycardia, sensory desensitization) and effects on the central nervous system (NIOSH, 1973:37-39). However, epidemiological

studies on occupational exposure to TCE fail to show any link between TCE and the increased occurrences of any malignancies (Spirtas et al, 1991:528).

### ***Exposure Assessment***

A description of the epidemiological study performed at Hill Air Force Base as it pertains to this research, methods for estimating historical exposure, and relevant issues in modeling are presented.

***Hill AFB Epidemiological Study.*** The Hill AFB epidemiology study was undertaken as result of actions by Hill AFB employees and their union, the American Federation of Government Employees (AFGE) Local 1592. On 2 March 1978, one present and two former Hill AFB employees filed a claim under the Federal Tort Claims Act alleging that the United States Air Force had "knowingly and intentionally furnished to claimant for use in the performance of his duties dangerous and poisonous substances and knowingly and intentionally failed to provide proper and adequate safety measures (Bayer et. al., 1978:79)." Immediately following this formal suit against the Air Force, it was made publicly known that there also existed a formal complaint filed with the AFGE Local 1592, which alleged that exposure to toxic chemicals had contributed to the death or illness of 44 workers. Two days following this public announcement, the President of the AFGE Local 1592, Mr. Breeden, in a letter to the OO-ALC/CC, stated that "he believed that toxic chemicals or other agents harmful to employee health had or was being utilized within portions of [the Maintenance Directorate], Building 100 (Bayer et. al., 1978:79)." The Air Force responded by

sending a staff assistance visit team composed of members from Hq USAF/SGPA, AFLC/SGB, AFLC/MAXF, the USAF Occupational and Environmental Health Laboratory, the National Institute for Occupational Safety and Health, and the Department of Health, Education and Welfare (Bayer et. al., 1978:79-80). Upon visiting the base, reviewing historical records, and interviewing employees, the Air Force/NIOSH Staff Assistance Team's primary recommendations were to establish and further improve management practices concerning worker training, exposure assessment, grievance procedures, and the worker medical program. It was also recommended that a statistical analysis of past and present cancer cases existing in workers be carried out. In January 1982, in response to the team's recommendations and mounting political and union pressure, the National Cancer Institute was contracted to perform a retrospective mortality study of 14,457 civilian workers who had been employed at Hill AFB for at least one year between 1952 and 1956. During that same year, the Rocky Mountain Center for Occupational and Environmental Health of the University of Utah School of Medicine was performing a study to determine the feasibility of morbidity research at the base. Their final report, "Report on the Feasibility of Morbidity Health Research at Hill Air Force Base, Utah", by the Rocky Mountain Center for Occupational and Environmental Health, Departments of Internal, and Family and Community Medicine, University of Utah School of Medicine, Salt Lake City, Utah 84112, NIOSH Health Hazard Evaluation Cooperative Agreement 1-UO1-OH-01249-01, January 1983, made several recommendations as to possible

morbidity research that could be performed on the base. However, no research into this area was performed.

The primary goal of NCI's retrospective mortality study was to determine if any relationship existed between exposure to TCE and specific causes of death (Spirtas et al., 1991:516). Resultant findings of the study are listed in Tables 1-4 of Appendix A. The task of determining the exposures was carried out by two industrial hygienists, J.S. Lee and D.E. Marano. They performed shop inspections, personnel interviews and historical record and document reviews. Evaluation of this data led to the establishment of a job dictionary consisting of approximately 43,000 job and organization codes. From this job dictionary, qualitative and some quantitative estimates of exposures were made for combinations of specific jobs within an organization or shop. Jobs were classified according to whether exposure was intermittent or continuous, frequent or infrequent, and low level or peak (Spirtas et al., 1991:517).

For TCE and mixed solvents, exposure levels were estimated by first determining frequency and duration of use of the solvents based on information obtained from worker position descriptions, technical orders, and historical shop files. These results are shown in Table 2. Secondly, exposure indices were assigned which reflected the relative differences in TCE exposure levels which existed throughout time. Table 3 contains these results. Using this information, indexes of cumulative exposures were calculated by using the following relationship (Stewart et al., 1991:535):

$$I = (f)(d)(i)/480$$

f = frequency of use (Table 2)

d = duration of use (Table 2)  
i = index of exposure (Table 3)  
480 = number of minutes in eight hours

Specifically, cumulative exposure is the product of the index *I* and the number of years spent at each job. Thus, if an individual had worked from 1957-1958 as a pneudraulic systems mechanic for 300 days with frequent exposures to TCE, his index of exposure, *I*, for that period would equal  $20.5 = 2 \times 15 \times 400 \times 300 / (480 \times 365)$ . Summation of all *I*'s for all jobs held would yield the cumulative score. The cumulative score would then be divided by the total number of years the individual was exposed, thus yielding the average index which was used in the mortality analysis (Spiras et al., 1990:5-6).

**Table 2. Frequency and Duration of Use of TCE and Mixed Solvents (Stewart et al.,1991:535).**

| Types of Job                         | Frequency (f)             | Duration (d), min. |
|--------------------------------------|---------------------------|--------------------|
| Benchwork<br>(low level exposures)   | Continuous, about 15/day  | 5                  |
|                                      | Intermittent, about 4/day | 5                  |
| Vapor degreasing<br>(peak exposures) | Frequent, 2/day           | 15                 |
|                                      | Infrequent, 0.4/day       | 15                 |

**Table 3. Indices Used in Exposure Estimation (Stewart et al., 1991:535).**

| Period    | Peak (TCE) | Low Level (TCE) | Mixed Solvents |
|-----------|------------|-----------------|----------------|
| 1939-1954 | 600        | 10              | 10             |
| 1955-1967 | 400        | 10              | 10             |
| 1968-1978 | 200        | 0               | 10             |
| 1979-1983 | 0          | 0               | 10             |

**Note:** Use of TCE was eliminated from the base as a cold solvent in 1968 and as a degreasing solvent in 1978.

From their study, NCI concluded that "there were no significant or persuasive relationships between various measures of exposure to TCE and the risk of any specific malignancy" (Spirtas et al., 1990:30). Though limitations exist in this study, (i.e. quantification of exposure, low levels of exposure, and small numbers of deaths for some causes) it remains the largest study of industrial exposure to TCE with 7282 persons exposed (Stewart et al., 1991:536). Additionally, the conclusions reached by NCI are consistent with other epidemiology studies of persons exposed to TCE (Spirtas et al., 1991:528).

***Estimating Historical Exposures.*** Accurately estimating historical exposure levels of potential hazardous agents is important because the "true test" of long term effects of human exposure to that agent are often provided by results of epidemiological studies (Nurtan, 1979:58). Specifically, for occupational exposure, the retrospective cohort study is the most widely used type of epidemiological study performed in the evaluation of potential hazardous agents found in industrial occupational settings (Monson, 1990:51). The process of determining historical exposures is usually carried out by industrial hygiene researchers and, more often than not, proves to be a difficult task at best (Smith et al., 1991:441).

Assessing exposures, regardless of whether they are present or historical, is accomplished by three general approaches or combinations thereof. The first is the predictive approach, which is characterized by estimating the distributions of chemicals encountered in the environment in conjunction with the activity patterns



of the exposed individual. The second approach entails inferring exposure levels based on observed levels of contaminants and metabolites observed in biological fluids and tissues of the exposed individual and is called the reconstructive approach. The final means, the direct approach, is the most straightforward and simply involves real-time measurement of exposure levels actually experienced by individuals (Whitmyre et al., 1992:297).

Within the boundaries described by these three approaches exist methods for assessing purely historical exposure levels. Two conceptual models which are identified as the source-receptor model and the task-TWA (time-weighted average) model of full-shift exposures provide the foundation for which most historical exposure assessments are based (Smith et al., 1991:441).

The source-receptor model involves the formal process by which the researcher, usually an industrial hygienist, exercises professional knowledge-based decision processes to analyze the situation and determine an appropriate exposure. Such a process typically includes record reviews to establish jobs held and areas worked by members of the cohort, tasks and resultant exposures associated with each job, reviews of historical exposure estimates and monitoring data, observations of present day activity patterns, physical layouts, work practices, etc., and finally, the synthesis of this and all other pertinent available information into an estimate of exposure (Stewart et al., 1986:34). Further classification of the source-receptor concept methodology leads to a categorization of the methods based on the general exposure experience of the cohort. Essentially, this means

that the estimate of a particular historical exposure is based on an analysis of a common parameter of exposure such as occupation or industry, exposure zone, task, or any combination of parameters (Stewart et al., 1986:34). Forms of this type of analysis were used by Stewart et al. in the Hill study.

The task-TWA model is used to develop historical exposure estimates based on full-shift exposures. This is done by developing a chronological matrix which details changes in practices, equipment, or anything that would result in a definable change in exposure. Coupled with limited monitoring data, this method yields very good results when used to determine TWA exposures from short term task data involving high exposure levels (Smith et al., 1991:441). Evidence of use of this type of approach is also found in the Hill study.

***Exposure Modeling.*** Though methodologies and models are available which provide a means of retrospectively assessing occupational exposure, difficulty still exists largely due to lack of available historical exposure and industrial hygiene data existing prior to the mid-1970's (Stewart et al., 1986:34). For this reason, estimation of exposure by modeling of known physical phenomena is used as an aid to facilitate source-receptor conceptual modeling. The majority of these indoor air models are based on a basic mass continuity equation, which in its simplest form, equates the rate of increase of a contaminant in a defined volume to the difference between the rates which the contaminant enters and leaves the volume (Masters, 1991:238). The sophistication and complexity of each model is directly proportional to the degree to which the major factors affecting personal

exposure are addressed. The major factors which best describe personal exposure are individual activity patterns, characteristics of the model space (e.g. HVAC systems, filtration, infiltration, reactivity, cross drafts, room size and geometry, etc.), and source characteristics (e.g. emission rates, operating rates and methods, utilization rates, etc.) (Franke et al., 1990:765). Utilization of some of these factors can be seen in the mass balance equation used in the personal air quality model (PAQM) developed by Systems Applications, Inc. shown below (Hayes, 1989:1454):

$$V \frac{dC}{dt} = \underbrace{kQ_M(C_0 - C)}_{\text{Infiltration}} + \underbrace{kQ_F(E_F C_0 - C)}_{\text{Outdoor Makeup Air}} + \underbrace{kQ_R(E_R - 1)C}_{\text{Recirculation}} - \underbrace{kKAC}_{\substack{\text{Surface} \\ \text{Reactivity} \\ \text{Losses}}} + \underbrace{S(t)}_{\text{Indoor Sources}}$$

where:

$C_0$  = outdoor concentration

$C$  = indoor concentration

$V$  = building volume

$Q_F$  = volumetric infiltration rate

$Q_R$  = volumetric flow rate of recirculated air

$Q_M$  = volumetric flow rate of makeup air

$E_F$  = filter efficiency

$E_R$  = efficiency of the recirculation

$k$  = mixing factor

$S(t)$  = indoor source generation term

$K$  = pollutant reactivity factor

$A$  = interior surface area

Variations of this mass balance equation have been used in models developed by various other researchers such as Franke et al., McKone and Knezovich, Wadden et al., and Pedelty and Holcomb. For further reference, refer to the listing in the bibliography for each respective author.

Three of the more commonly used mass balance models are (1) the completely mixed reactor model, (2) the multi-point diffusion model, and (3) the multi-point diffusion model with advection (Franke et al., 1990:765). Model 1 assumes well-mixed conditions and is described by an equation of the form of that used in the PAQM model. Model 2 considers the interior space or volume to be a near infinite hemisphere or semi-hemisphere bounded by the dimensions of the space and centered at the emission source. Air movement is not affected by external influences, and is thus considered to be random. Under these circumstances, eddy diffusion is the primary dispersion mechanism which results in uniform decreasing of contaminant levels as the radial distance from the source is increased. Equation (1) describes this model and represents the solution to the mass balance on hemispherical space, ignoring surface deposition (Franke et al., 1990:766):

$$C = [S/(2\pi \times D \times r)]\text{erfc}[r/(4 \times D \times t)^{0.5}] \quad (1)$$

where:

$C$  = concentration at any location (mass/volume)

$r$  = radius of hemisphere at any time,  $t$  (length)

$S$  = steady state emission rate of source (mass/time)

$D$  = eddy diffusivity (area/time)

$\text{erfc} = 1 - \text{the error function}$

Given two simultaneously collected samples over the same averaging time,  $t_{av}$ , at two distances  $r_1$  and  $r_2$ , the integral form of equation (1) yields two independent equations, (2) and (3), which can be solved simultaneously for  $D$  and  $S$ , thus allowing computation of the average area concentration (Wadden et al., 1989:4089):

$$C_{av,r1} = \int_0^{t_{av}} [S/(2\pi \times D \times r_1)] \text{erfc}[r_1/(4 \times D \times t)^{0.5}] dt/t_{av} \quad (2)$$

$$C_{av,r2} = \int_0^{t_{av}} [S/(2\pi \times D \times r_2)] \text{erfc}[r_2/(4 \times D \times t)^{0.5}] dt/t_{av} \quad (3)$$

The third model is most applicable when the interior air of the model volume is disturbed by external factors such as strong and sustained cross-drafts. When unidirectional advection disturbances of this sort are present, the equation describing model 3 exists in Gaussian plume form, which traditionally has been used in ambient air pollution modeling (Franke et al., 1990:766):

$$C = [S/(2\pi \times D \times x)] [\exp(-u \times y^2/(4 \times D \times x))] [\exp(-u \times z^2/(4 \times D \times x))] \quad (4)$$

where:

$u$  = cross draft velocity in the  $x$  direction

Most situations can be described to some extent by one of the presented models above. In choosing a model, it is important the model closely describes the actual indoor environment being tested. Thus, it becomes just as important to

select exposure parameters which closely describe the indoor environment (Franke et al., 1990:767).

Traditionally, exposure parameters have been point estimators and represented "worst-case" or "typical" values which were one point on the distribution curve of that particular parameter (Whitmyre et al., 1992:298-301). However, the need to address the fact that workers and industrial environments are not constants and are more realistically described by stochastic means has resulted in the use of methods which address this variability. One of the more commonly used techniques is Monte Carlo simulation (Thompson et al., 1992:53-54). By using probability distribution functions instead of point estimators to describe the exposure model parameters, uncertainty and both individual and environmental variability are better addressed (Droz et al., 1989:447-448).

### **III. Methodology**

#### ***Introduction***

This section will briefly describe the manner in which the research objectives of this research were investigated. These objectives are defined within the investigative questions below:

1. Does sufficient information exist to model historical exposures found in the Hill AFB epidemiology study performed by Spirtas et al?
2. What type of model will best estimate this exposure?
3. What quantitative exposure levels result from applying such a model?

***Objective 1.*** In order to determine whether sufficient information and data were available to model the historical exposures experienced by workers at Hill AFB, it was necessary to visit the base. During the seven day period I was at the base, I reviewed historical records of the Maintenance Directorate kept by the Base Historian, the Civil Engineering Flight, and the Bio-Environmental Engineering Flight, conducted a walk through of existing shops, and interviewed the industrial hygienist who performed the exposure assessments of the original study, Mr. D.E. Marano. Types of records included photographs, base year books, Bio-Environmental Engineering shop files, workers compensation claims, press reports, official correspondence, industrial hygiene surveys, and engineering drawings. Walk throughs of shops were conducted to get a visual understanding of the operations, processes, and work practices that took place within various shops. During these walk throughs I also talked to older employees to try to get

a firsthand account of how the working environment had changed during the time they had been employed there. Finally, the interview with Mr. Marano also included a review of his files which he had developed while performing his historical exposure assessment of the Hill AFB aircraft maintenance workers.

**Objective 2.** Using the historical monitoring data obtained, Monte Carlo simulation will be used to estimate TCE intake levels, TWA (time weighted average) exposure concentrations, cumulative exposure levels, and LCRs (lifetime cancer risks). This will be accomplished using a spreadsheet and @RISK, simulation and modeling software from Palisade Corporation.

**Objective 3.** Concentration levels in the immediate work area of vapor degreaser operators will be estimated using physical phenomena modeling. Because the exposure being modeled is based on a specific task performed by similar individuals, the source-receptor concept will be employed. Specifically, exposures zones will be determined and concentration levels within those zones will be modeled using the multi-point diffusion model described by equations (1), (2), and (3).



#### ***IV. Analysis and Results***

##### ***Introduction***

Presentation and discussion of the results of this research are presented in detail below.

##### ***Feasibility of Reconstructive Modeling***

As noted by Stewart et al., I found there to be basically only two types of exposure to TCE which the aircraft maintenance workers were subjected to. The first occurred during the use of TCE as a cold state solvent where it was dispensed from containers or plastic bottles directly unto the surface of a part to be cleaned or unto a rag, which was then used to clean that part. Very little information and no exposure measurements were available for this type of exposure until the late 1970's. At this point however, the solvent used was 1,1,1 trichloroethane, as the use of TCE as a cold state solvent for most benchwork applications had ceased in 1968. The second type of exposure resulted from the use of vapor degreasers. Substantially more information was available relating to vapor degreaser operations. Monitoring data was available to various extents for each shop. Most reported levels were either instantaneous measurements taken with a Miran infrared analyzer or average concentration measurements collected over short time periods using pumps and collector tubes.

Because of the lack of information available regarding usage of TCE as a cold state solvent for benchwork combined with the finding that no trichloroethane exposure levels exceeding 60 ppm for benchwork were discovered, modeling of

this exposure route will not be pursued. However, sufficient information was available to attempt reconstruction of exposures resulting from usage of vapor degreasers. Specifically, information and monitoring pertaining to vapor degreasers found in the Wheels and Brakes Shop and Struts Shop was the most abundant. Information and monitoring data on other shops was available, however, it was very limited. Hence, the modeling of the exposure of vapor degreaser operators assigned to these shops is the only exposure which I believe can be modeled and substantiated.

**Results.** Very little monitoring data was found for shops other than the Struts and Wheels and Brakes shops. Prior to the mid to late 1970's, recorded monitoring data for individual shops seemed to be sporadic at best. The majority of the monitoring data obtained for the aforementioned shops was taken in 1978 and 1979 and was in response to the legal proceedings brought against the Air Force by Hill AFB employees and their union, the AFGE Local 1592. Though extensive monitoring was not performed prior to this time, an industrial hygiene program did exist. Annual surveys describing work practices and equipment conditions were undertaken with some regularity beginning in the early to mid sixties.

**Shop Details.** Both the Struts shop and the Wheels and Brakes shop were located in building 205 in 1954. The Wheels and Brakes shop remained there until 1980 when it was relocated to building 507, whereas the Struts shop was relocated to building 264 in 1964 and remained there through September 1979 when it was also moved to building 507. Neither building 264 nor 205 presently exists. Both buildings

were constructed of wood and masonry in the early 1940's. Similar in design (A-frame), each building resembled a small hangar. Descriptions from clinical records describe both buildings as having "a large open area with good natural ventilation." The description continues with "the doors and windows were kept closed in the winter months but vehicle entrances were opened periodically to allow vehicles to enter the building." The primary operation of the Struts shop was the disassembly, refurbishment, and rebuilding of aircraft struts, with the exception of C-5 struts, which were serviced by a separate C-5 only struts shop located in building 510. TCE vapor degreasers were used in two locations in the Struts shop - the magnaflux area and the parts buildup and testing area. The Wheels and Brakes shop had a similar mission as the Struts shop, only aircraft wheels and brakes as opposed to struts were cleaned, inspected, disassembled, and reassembled. TCE vapor degreasers were used specifically by workers in the magnaflux and brake and wheel disassembly sections of the shop. References to the duration and frequency of use of the tanks for both shops were found in clinical records and industrial hygiene surveys. These sources specified the degreasers were used for time periods ranging from twice daily for a total of thirty minutes to two hours per day.

***Monitoring Data.*** All monitoring results found in the industrial hygiene files of both shops along with those of building 510 are listed in Appendix A. All breathing zone monitoring results for these shops are listed in Table 4. The remarks section of Table 4 consists of any information which was found with that specific monitoring result.


**Table 4. TCE Breathing Zone Concentration Levels of Vapor Degreaser Workers.**

| Date     | Building | Sample Location | Instrument Used | Conc. (ppm) | Remarks                                     |
|----------|----------|-----------------|-----------------|-------------|---|
| 09/22/65 | 264      | NS              | NS              | 100         |   |
| 05/18/68 | 264      | NS              | NS              | 100         | heated degreaser                            |
| 05/18/68 | 264      | NS              | NS              | 250         |   |
| 04/09/73 | 205      | NS              | NS              | 0.5         |   |
| 09/25/75 | 264      | 60              | Charcoal T.     | 145         |   |
| 04/12/76 | 264      | NS              | NS              | 300         |   |
| 04/27/76 | 205      | NS              | NS              | 5           |   |
| 08/16/76 | 264      | NS              | NS              | 500         | cross drafts, fans pulling vapors from tank |
| 08/16/76 | 264      | NS              | NS              | 400         | same as above, lid closed                   |
| 12/21/77 | 205      | NS              | Draeger T.      | 500         | door to E. of machine opened -cross drafts  |
| 12/21/77 | 205      | NS              | Draeger T.      | 350         |   |
| 04/21/78 | 264      | NS              | NS              | 125         | during spray lance use                      |
| 04/26/78 | 264      | NS              | NS              | 450         | during spray lance use                      |
| 04/28/78 | 264      | NS              | NS              | 350         | during spray lance use                      |
| 05/18/78 | 264      | NS              | Draeger T.      | 75          |   |
| 09/07/78 | 264      | NS              | NS              | 489         | average while removing parts from VD        |
| 09/07/78 | 264      | NS              | NS              | 132         | average while placing parts in VD           |
| 09/07/78 | 264      | NS              | NS              | 620         | peak while placing parts in VD              |
| 09/07/78 | 264      | NS              | NS              | 0           | low while placing parts in VD               |
| 09/07/78 | 264      | NS              | NS              | 1000        | peak while removing parts from VD           |
| 09/07/78 | 264      | NS              | NS              | 25          | low while removing parts from VD            |
| 09/07/78 | 264      | NS              | NS              | 9           | from worker in magnaflux area               |
| 09/25/78 | 510      | 32              | Charcoal T.     | 620         |   |
| 09/25/78 | 510      | 30              | Charcoal T.     | 470         |   |
| 10/01/78 | 264      | NS              | Miran IR        | 100         | removing parts from VD @ 11 fpm             |

**Table 4 (continued). TCE Breathing Zone Concentration Levels of Vapor Degreaser Workers**

| Date     | Building | Sample Location | Instrument Used | Conc. (ppm) | Remarks                                 |
|----------|----------|-----------------|-----------------|-------------|---|
| 10/01/78 | 264      | NS              | Miran IA        | 155         | lowering parts into vapor layer of VD   |
| 10/01/78 | 264      | NS              | Miran IA        | 200         | during spray lance use                  |
| 11/06/78 | 510      | 255             | Charcoal T.     | 29          |   |
| 11/06/78 | 510      | 132             | Charcoal T.     | 54          |   |
| 01/05/79 | 510      | NS              | Miran-IA        | 300         | inst. limit, during spray lance use     |
| 01/05/79 | 510      | NS              | Miran-IA        | 300         | inst. limit, parts removed from tank    |
| 01/05/79 | 510      | NS              | Miran-IA        | 300         | inst. limit, during spray lance use     |
| 01/05/79 | 510      | NS              | Miran-IA        | 180         | Idle tank                               |
| 01/05/79 | 510      | NS              | Miran-IA        | 180         | idle tank                               |
| 01/05/79 | 510      | NS              | Miran-IA        | 175         | after 4 strut pistons lowered into tank |
| 01/05/79 | 510      | NS              | Miran-IA        | 270         | parts lowered into tank                 |
| 03/08/79 | 510      | 25              | NS              | 235         | 2' above tank while work performed      |
| 03/08/79 | 510      | 10              | NS              | 200         | 2' above tank after work performed      |
| 03/08/79 | 510      | 20              | NS              | 320         | 2' above grated area on tank            |
| 03/29/79 | 264      | 120             | NS              | 1           |   |
| 03/29/79 | 205      | NS              | Miran-IA        | 80          | 5' above work platform                  |
| 03/29/79 | 264      | 480             | NS              | 13          |   |
| 03/29/79 | 264      | 145             | NS              | 2           |   |
| 03/29/79 | 205      | NS              | Miran-IA        | 285         | 2' above tank opening                   |
| 03/29/79 | 264      | 205             | NS              | 15          |   |
| 03/29/79 | 264      | 232             | NS              | 33          |   |
| 03/29/79 | 264      | 140             | NS              | 45          |   |
| 03/29/79 | 264      | 110             | NS              | 37          |   |
| 04/12/79 | 205      | NS              | NS              | 285         | 2' above tank                           |
| 04/12/79 | 205      | NS              | NS              | 80          | 5' above tank                           |
| 12/21/79 | 205      | NS              | NS              | 500         | tank lid open                           |
| 12/21/79 | 205      | NS              | NS              | 350         | tank lid closed                         |

The histogram shown in Figure 2 shows the relative frequencies of the breathing zone concentrations given in Table 4. Descriptive statistics are listed in Table 5.



**Figure 2. Distribution of Breathing Zone Concentration Data.**

**Table 5. Descriptive Statistics of Breathing Zone Concentration Data.**

| Statistic                              | Value  |
|--|--------|
| Mean                                   | 210.58 |
| Std. Error of Mean                     | 24.85  |
| Standard Deviation                     | 177.43 |
| Median                                 | 180    |
| Lower Limit of 95% Confidence Interval | 160.67 |
| Upper Limit of 95% Confidence Interval | 260.48 |

The majority of the breathing zone samples were taken between 1978 and 1979. As a group, the samples represent all possible exposure scenarios (i.e. lowering parts into tank, removing parts from tank, idle tank, open tank, closed tank, spray lance use) associated with the use of the vapor degreasers. Only approximately 20 percent of the

samples were taken prior to 1978. However, during the time between 1954 and 1979, no major changes occurred in either shop's operations or the operation of other degreasers located on base which would suggest that this distribution would not be representative of exposure levels experienced throughout the entire period of concern. Reduction in exposure as a result of increased controls and equipment improvements did not become a major factor until both shop functions were relocated to new and more modern facilities beginning in late 1979. During this same time period, TCE was replaced by trichloroethane as the primary vapor degreaser solvent used (Stewart et al., 1991:534). Evidence supporting the premise that exposures over this 25 year time period were relatively the same manifests itself in work condition descriptions found in annual Bio-Environmental Engineering surveys and clinical records. References from these documents regarding ongoing ventilation and equipment problems (e.g. insufficient building makeup air, no local exhaust systems for degreasers, cross drafts removing vapors from degreasers) can be found dating well into the mid 1970's. More importantly, a pattern of worker behavior existing through the mid 1970's can be seen which indicates a lack of proper training in degreaser operations or simply an unwillingness to exercise proper procedures. The most common problems found in the majority of surveys were failure to close degreaser lids when not in use, failure to properly wear protective equipment, failure to use spray lance in full conjunction with the local exhaust system, and operation of basket hoists at excessive speeds. These problems were primarily supervisory and training related and existed until the mid to late 1970's when the industrial hygiene programs and recommendations of the

Bio-Environmental Shop began to be seriously implemented and followed by management and workers.

**Summary.** Workers performing vapor degreaser operations throughout the base performed the same type operations in similarly designed and equipped buildings. This suggests that mean exposures in such defined areas are dictated by similar exposure-modifying variables. When these variables are relatively constant, the mean of an exposure distribution would not be expected to change over time (Yu et al., 1990:194). Because evidence exists showing the major factors affecting exposure levels were existent in the latter half of the 25 years, it can be inferred that those same factors also existed during the first half of the 25 year period. As such, the distribution of breathing zone concentrations shown in Figure 2 is a valid representation of exposures experienced by personnel performing vapor degreaser operations and will be used as the input concentration distribution in the Monte Carlo simulation analysis.


#### ***Monte Carlo Simulation Analysis***

**Background.** Estimating a historical exposure is difficult because of the lack of available information. Usually this forces us to make assumptions about the various parameters we are concerned with. When these assumptions are made using point estimators, the possibility exists that our assumptions may vary greatly from the parameter's true value. To compensate for this uncertainty, estimates are most often selected based on average, conservative, or worst-case values. This method has its limitations. Monte Carlo simulation is one means of avoiding the problems associated




with point estimators. Monte Carlo simply refers to the traditional method of sampling random variables in simulation modeling. The first step in the simulation is to choose probability distribution functions (PDFs) which describe the uncertain variables used in the simulation or model. These variables, thus, take on a range of values with known probability. Once all variables and constants to be used in the exposure model are defined, a computer program (@Risk by Palisade was used for all simulations in this research) is used to draw a random variable from each PDF used in the model. Modeled variables are then computed using the drawn random variables. This process is repeated a large number of times to produce complete distributions of the modeled variables.


**Results.** Three different probability distribution functions were fitted to breathing zone concentrations. The distributions used were chosen based on "goodness-of-fit." Specifically, the Weibull(0.96,275) distribution best approximated the breathing zone concentration data based on the chi-square test. The data was best fit by a normal(211,177) distribution when the measure of goodness-of-fit was the Anderson-Darling test. The triangle(0,0,620) distribution placed relatively high on both these tests. Graphs of these distributions as well as comparisons with the breathing zone concentration data are presented in Figures 3-8.




**Figure 3. Normal Approximation of Breathing Zone Concentration Data.**




**Figure 4. Difference in Normal Approximation and Breathing Zone Concentration Data**




**Figure 5. Weibull Approximation and Breathing Zone Concentration Data.**



**Figure 6. Difference in Weibull Approximation and Breathing Zone Concentration Data.**



**Figure 7. Difference in Triangle Approximation and Breathing Zone Concentration Data.**



**Figure 8. Difference in Triangle Approximation and Breathing Zone Concentration Data.**

Neither the Weibull nor the triangle distribution approximated the breathing zone concentration data well at the tails of the distribution. As a result, neither was used as an estimation of the breathing zone concentration distribution. Instead, the breathing zone concentration was modeled using the normal distribution and the actual histogram of the breathing zone data. Table 6 contains distributions and parameters used in the Monte Carlo simulation of lifetime cancer risk (LCR), TWA, cumulative TWA, and TCE inhalation intake.


**Table 6. Description of Model Parameters.**

| Variable  | Distribution Description           |
|---|------------------------------------|
| Body Weight (BW) (lbs)                                    | Lognormal2(5.13,0.17) <sup>1</sup> |
| Exposure Frequency (EF) (days/yr)                         | Triangle(240,250,260)              |
| Exposure Time (ET) (min/day)                              | Uniform(30,120)                    |
| Exposure Duration (ED) (years)                            | Uniform(1,25)                      |
| Inhalation Rate (IR) (m <sup>3</sup> /day)                | 20                                 |
| Averaging Time (AT) (years)                               | 70                                 |
| TCE Cancer Slope Factor (SF)<br>(mg/kg-day) <sup>-1</sup> | 1.17e-2                            |


<sup>1</sup>Lognormal2 specifies a lognormal distribution where the entered mean and standard deviation equal the mean and standard deviation of the corresponding normal distribution. The arguments entered are the mean and standard deviation of the normal distribution for which an exponential of the values in the distribution was taken to generate the desired lognormal distribution.

Annual TWA concentration exposures were calculated on an 8 hour work day basis and are defined as the result of the exposure duration divided by 480 (number of

minutes in an 8 hour work day) times the exposure frequency. Figures 9 and 10 show the results of the simulation.




**Figure 9. Annual TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Normal Distribution.**



**Figure 10. Annual TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Histogram Generated by the Breathing Zone Concentration Data.**


When the breathing zone concentration was modeled using the normal distribution, the mean annual TWA was 23.1 ppm. The 50th and 95th percentile values were 20.0 ppm and 54.8 ppm, respectively. When the distribution of the actual breathing zone concentration data was used, the mean annual TWA was 20.5 ppm. The 50th and 95th percentile values were 15.0 ppm and 57.4 ppm, respectively. Cumulative TWAs in which the cumulative integrated weighted exposure over the range of possible years a worker performing degreaser operations could have worked were calculated by summing the annual TWA exposures over the number of years worked. These results are shown in Figure 11.



**Figure 11. Cumulative TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Normal Distribution.**

The mean cumulative TWA exposure was 302 ppm. The 50th and 95th percentiles were 215 ppm and 892 ppm, respectively. Using the histogram of the actual breathing zone concentration data as the input to the model resulted in a mean cumulative TWA exposure of 265 ppm. The 50th and 95th percentile values were 158 ppm and 919 ppm,

respectively. The distribution of TWAs resulted from this simulation are shown in Figure 12. Higher values are representative of exposures experienced when a worker performed degreaser operations for the majority of the 25 years.



**Figure 12. Cumulative TWA Concentration Exposure Calculated with Breathing Zone Concentrations Modeled Using the Histogram Generated by the Breathing Zone Concentration Data.**


Daily inhalation intake amounts of TCE were calculated using equation (5).

$$Intake = \frac{CA \times IR \times ET \times EF \times ED}{BW \times AT} \quad (5)$$


The distribution of the inhalation intake values are shown in Figures 13 and 14. Using the normal distribution as the input to the simulation, the mean value of TCE intake through inhalation was 6.7 mg/kg-day. The 50th and 95th percentile values were 4.7 mg/kg-day and 19.8 mg/kg-day, respectively. Using the histogram of the breathing zone



data as the concentration input resulted in a mean intake of 5.9 mg/kg-day. The 50th and 95th percentile values were 3.4 mg /kg-day and 20.4 mg/kg-day respectively.




**Figure 13. TCE Inhalation Intake (mg/kg-day) with Breathing Zone Concentrations Modeled Using the Normal Distribution.**




**Figure 14. TCE Inhalation Intake (mg/kg-day) with Breathing Zone Concentrations Modeled Using the Histogram Generated from the Breathing Zone Concentration Data.**

Multiplying the inhalation intake by the cancer slope factor for TCE produces a unitless probability which reflects the cancer risk associated with that dosage. Figures 15 and 16 show the risks and associated probabilities of that risk.



**Figure 15. Cancer Risk with TCE Inhalation Intake (mg/kg-day) Calculated Using the Normal Distribution to Model Breathing Zone Concentrations .**



**Figure 16. Cancer Risk with TCE Inhalation Intake (mg/kg-day) Calculated Using the Histogram of Breathing Zone Concentration Data.**

The risks resulting from modeling the breathing zone concentration with a normal distribution fell between  $3.6 \times 10^{-5}$  and 1.0 with a mean value of 0.11. The 50th and 95th percentile values were 0.08 and 0.34, respectively. Using the histogram of the actual breathing zone concentration data resulted in a distribution with a maximum risk of 0.9 and a minimum risk of  $2.7 \times 10^{-6}$ . The 50th and 95th percentile values were 0.06 and 0.35, respectively. The LCRs produced are conditionally based on several variables and by no means imply that all possible uncertainties are accounted for. Uncertainties associated with the accuracy of the monitoring data, the population intake parameters, toxicity extrapolation techniques, and other factors prevent acceptance of the LCRs as being definitive. Instead, it is intended that the LCRs provide a reference from which to make comparisons and general inferences.

Summary statistics for all outputs discussed are presented in Table 7.

**Table 7. Summary Statistics for Outputs of Monte Carlo Simulation of Exposure to Degreaser Breathing Zone Concentrations Only.**

| Parameter                | Inhalation Intake     |                       | Lifetime Cancer Risk |           | Annual TWA Exposure |           | Cumulative TWA Exposure |           |
|--------------------------|-----------------------|-----------------------|----------------------|-----------|---------------------|-----------|-------------------------|-----------|
| Distribution             | Normal                | Histogram             | Normal               | Histogram | Normal              | Histogram | Normal                  | Histogram |
| Units                    | (m <sup>3</sup> /day) | (m <sup>3</sup> /day) |                      |           | ppm                 | ppm       | ppm                     | ppm       |
| Minimum=                 | 0                     | 0                     | 3.64E-05             | 2.66E-06  | 0.01                | 0         | 0.13                    | 0.01      |
| Maximum=                 | 63.9                  | 54.92                 | 1.09                 | 0.93      | 105.01              | 107.06    | 2175.45                 | 2133.3    |
| Mean=                    | 6.7                   | 5.87                  | 0.11                 | 0.1       | 23.1                | 20.46     | 302.32                  | 265.33    |
| Std Deviation=           | 6.64                  | 6.75                  | 0.11                 | 0.11      | 16.09               | 18.27     | 288.83                  | 297.84    |
| Variance=                | 44.16                 | 45.62                 | 0.01                 | 0.01      | 258.93              | 333.95    | 83420.42                | 88710.36  |
| Skewness=                | 1.92                  | 2.04                  | 1.92                 | 2.04      | 1.06                | 1.29      | 1.68                    | 1.88      |
| Kurtosis=                | 8.57                  | 8.21                  | 8.57                 | 8.21      | 4.24                | 4.52      | 6.57                    | 7.06      |
| <b>Percentile Values</b> |                       |                       |                      |           |                     |           |                         |           |
| 5Perc=                   | 0.45                  | 0.2                   | 0.01                 | 0         | 2.86                | 1.22      | 20                      | 9.1       |

**Table 7 (continued). Summary Statistics for Outputs of Monte Carlo Simulation of Exposure to Degreaser Breathing Zone Concentrations Only.**

| Parameter                | Inhalation Intake     |                       | Lifetime Cancer Risk |           | Annual TWA Exposure |           | Cumulative TWA Exposure |           |
|--------------------------|-----------------------|-----------------------|----------------------|-----------|---------------------|-----------|-------------------------|-----------|
|                          | Normal                | Histogram             | Normal               | Histogram | Normal              | Histogram | Normal                  | Histogram |
| Units                    | (m <sup>3</sup> /day) | (m <sup>3</sup> /day) |                      |           | ppm                 | ppm       | ppm                     | ppm       |
| <b>Percentile Values</b> |                       |                       |                      |           |                     |           |                         |           |
| 10Perc=                  | 0.77                  | 0.39                  | 0.01                 | 0.01      | 5.11                | 2.37      | 34.89                   | 18.2      |
| 15Perc=                  | 1.07                  | 0.62                  | 0.02                 | 0.01      | 7.2                 | 3.68      | 50.48                   | 29.19     |
| 20Perc=                  | 1.43                  | 0.89                  | 0.02                 | 0.02      | 9.2                 | 4.86      | 66.53                   | 41.79     |
| 25Perc=                  | 1.86                  | 1.18                  | 0.03                 | 0.02      | 11.05               | 6.18      | 87.24                   | 54.89     |
| 30Perc=                  | 2.35                  | 1.49                  | 0.04                 | 0.03      | 12.63               | 7.63      | 109.19                  | 68.76     |
| 35Perc=                  | 2.93                  | 1.87                  | 0.05                 | 0.03      | 14.48               | 9.14      | 134.92                  | 85.01     |
| 40Perc=                  | 3.47                  | 2.31                  | 0.06                 | 0.04      | 16.26               | 10.95     | 159.61                  | 106       |
| 45Perc=                  | 4.07                  | 2.81                  | 0.07                 | 0.05      | 18.09               | 12.94     | 186.52                  | 130.53    |
| 50Perc=                  | 4.69                  | 3.42                  | 0.08                 | 0.06      | 20.03               | 14.98     | 214.97                  | 158.01    |
| 55Perc=                  | 5.32                  | 4.1                   | 0.09                 | 0.07      | 22.08               | 17.4      | 246.65                  | 189.28    |
| 60Perc=                  | 6.1                   | 4.83                  | 0.1                  | 0.08      | 24.07               | 20.03     | 282.81                  | 222.4     |
| 65Perc=                  | 7.01                  | 5.61                  | 0.12                 | 0.1       | 26.45               | 23.24     | 322.79                  | 260.34    |
| 70Perc=                  | 7.99                  | 6.59                  | 0.14                 | 0.11      | 28.94               | 26.49     | 364.73                  | 303.9     |
| 75Perc=                  | 9.19                  | 7.98                  | 0.16                 | 0.14      | 31.75               | 30.01     | 419.43                  | 366.76    |
| 80Perc=                  | 10.81                 | 9.73                  | 0.18                 | 0.17      | 35.11               | 34.37     | 489.77                  | 447.11    |
| 85Perc=                  | 12.93                 | 11.98                 | 0.22                 | 0.2       | 39.2                | 39.4      | 585.26                  | 546.6     |
| 90Perc=                  | 15.75                 | 15.02                 | 0.27                 | 0.26      | 45.69               | 46.36     | 701.45                  | 676.14    |
| 95Perc=                  | 19.85                 | 20.44                 | 0.34                 | 0.35      | 54.77               | 57.39     | 892.1                   | 918.94    |

### **Multi-Point Diffusion Model Analysis.**

**Background.** Cleaning of parts in vapor degreasers by workers was performed as a task in support of their primary job as a parts disassembler or assembler. From the review of the Hill AFB records, daily time spent degreasing parts varied from 30 minutes to 2 hours. The remainder of the day was spent away from the degreaser performing their primary job function. Drawings and descriptions show that the vapor

degreasers were generally located near the center of a work section. Once parts were degreased, they were taken to other area within the section where the overhauling process was continued. Shop drawings indicate the remainder of the work could have taken place up to 50 feet from the actual vapor degreaser.

**Results.** Applying the data found in Table 8 to equations (1), (2), and (3), emission factors were developed for two open top vapor degreasers. One was located in building 510, while the other was located in building 264.

**Table 8. Two-Point Diffusion Model Parameters.**

| $C_{av,1}$<br>(g/m <sup>3</sup> ) | $C_{av,2}$<br>(g/m <sup>3</sup> ) | $r_1$<br>(meters) | $r_2$<br>(meters) | Bldg | Date     | Description                             |
|-----------------------------------|-----------------------------------|-------------------|-------------------|------|----------|---|
| 1.03                              | 0.15                              | 0.43              | 1.3               | 510  | 01/05/79 | after 4 strut pistons lowered into tank |
| 1.76                              | 0.16                              | 0.43              | 1.3               | 510  | 01/05/79 | during spray lance use                  |
| 1.58                              | 0.21                              | 0.43              | 1.3               | 510  | 01/05/79 | parts lowered into tank                 |
| 1.76                              | 0.21                              | 0.43              | 1.3               | 510  | 01/05/79 | during spray lance use                  |
| 1.76                              | 0.18                              | 0.43              | 1.3               | 510  | 01/05/79 | parts removed from tank                 |
| 1.06                              | 0.06                              | 0.43              | 1.3               | 510  | 01/05/79 | idle tank                               |
| 1.38                              | 0.15                              | 0.61              | 1.83              | 510  | 03/08/79 | heights above tank while work           |
| 1.17                              | 0.06                              | 0.61              | 4.57              | 510  | 03/08/79 | while work performed                    |
| 1.67                              | 0.47                              | 0.61              | 1.52              | 205  | 03/29/79 | heights above tank opening              |
| 0.1                               | 0                                 | 1.52              | 4.57              | 205  | 03/29/79 | front and side of tank                  |
| 0.44                              | 0                                 | 0.43              | 3.69              | 264  | 04/28/78 | NA                                      |

The averaging time used to calculate the emission factors was 0.25 minutes. Mathcad 4.0 for Windows was used to solve equations (2) and (3) simultaneously. The corresponding steady-state emission rate (S) and the eddy diffusivity (D) for each respective data pairing shown in Table 8 are tabulated in Table 9.

**Table 9. Eddy Diffusivities and Steady-State Emissions Resulting from Application of the 2-Point Diffusion Model Using the Data in Table 8.**

| <b>S<br/>(g TCE/min)</b> | <b>D<br/>(m<sup>2</sup>/min)</b> | <b>Description</b>                      |
|--------------------------|----------------------------------|---|
| 29.96                    | 7.47                             | after 4 strut pistons lowered into tank |
| 29.96                    | 3.7                              | during spray lance use                  |
| 41.21                    | 6.47                             | parts lowered into tank                 |
| 38.08                    | 5.11                             | during spray lance use                  |
| 32.1                     | 4.07                             | parts removed from tank                 |
| 12.42                    | 2.13                             | idle tank                               |
| 74.68                    | 8.63                             | heights above tank while work performed |
| 546.02                   | 105.66                           | while work performed                    |
| 307.66                   | 38.03                            | heights above tank openings             |
| 54.72                    | 1.66                             | front and side of tank                  |
| 3.39                     | 0.93                             | NA                                      |

Using the calculated eddy diffusivities and steady-state emission rates from Table 9, the predicted concentrations at distances ranging between 10 and 50 feet of the activity were calculated. The modeled concentrations are 30 minute average concentrations. Complete results are found in Table 10. Since the shops were designed such that the tear down and rebuilding of strut and brake parts occurred in work areas located away from the degreasing areas, predicted concentrations at these distances represent background levels a worker would experience in his work location resulting from another worker's performance of the activities described in Table 9. Using the diffusivity and emission rate values derived for the idle degreasing tank, daily ambient concentrations which would exist over an 8 hour workday were predicted. These results are also found in Table 10.

**Table 10. Predicted Concentrations at Various Distances from Degreasing Activities Using the Calculated Eddy Diffusivities and Steady-State Emission Rates Presented in Table 9.**

| Description                             | Concentration (ppm) at Distance From Activity |       |       |       |       |
|---|---|-------|-------|-------|-------|
|   | 10 ft   | 20 ft | 30 ft | 40 ft | 50 ft |
| <b>Averaging Time = 30 minutes</b>      |   |       |       |       |       |
| after 4 strut pistons lowered into tank | 28  | 11    | 6     | 3     | 2     |
| during spray lance use                  | 51  | 18    | 8     | 4     | 2     |
| parts lowered into tank                 | 44  | 17    | 9     | 5     | 3     |
| during spray lance use                  | 50  | 18    | 9     | 5     | 3     |
| parts removed from tank                 | 51  | 18    | 8     | 4     | 2     |
| idle tank                               | 33  | 10    | 4     | 2     | 1     |
| heights above tank while work performed | 62  | 25    | 13    | 8     | 5     |
| while work performed                    | 43  | 20    | 13    | 9     | 7     |
| heights above tank openings             | 65  | 29    | 17    | 12    | 8     |
| front and side of tank                  | 175   | 50    | 18    | 7     | 3     |
| NA                                      | 16  | 4     | 1     | 0     | 0     |
| <b>Averaging Time = 480 minutes</b>     |   |       |       |       |       |
| idle tank                               | 46  | 21    | 12    | 8     | 6     |

The steady-state emission rates derived from the monitoring data for various activities are not statistically significant because of the small sample size. They are, however, of the same magnitude as reported in the literature. Specifically, the emission rate for the idle degreaser described in Table 9 was calculated to be 12.42 g TCE/min. The open top area of the degreaser was 3.2 m<sup>2</sup>. Dividing the emission rate by the open top area yields an emission factor of 3.9 g TCE/m<sup>2</sup>-min. Wadden et al. reports the average emission factor for an open top degreaser to be 2.91 g TCE/m<sup>2</sup>-min. This value represents 9.5% of the total degreaser emissions. The remainder of the emissions were

captured and removed by local exhaust systems. Thus, the total degreaser release was 30.94 g TCE/m<sup>2</sup>-min. This value falls between 16.3 g TCE/m<sup>2</sup>-min reported by Dow and 54.8 g TCE/m<sup>2</sup>-min reported by the EPA for open top, uncontrolled, heated vapor degreasers. The agreement between the literature reported values and the calculated value as well as the fact that convergent solutions were found for equations (2) and (3) for all radius pairs suggests the model reflects the physical situation for the associated circumstances.

Using the background concentration modeling results in conjunction with the breathing zone concentration modeling results allows one to estimate the total exposure of a worker as a result of the combination of both exposures. In estimating the total exposure, the breathing zone concentrations were modeled using the normal distribution exactly as they were previously. The background concentrations which result from an idle tank, as given in Table 10, were used. The daily duration of exposure to the background concentration levels was determined by subtracting the degreaser breathing zone exposure duration time from eight hours (workday length). All other parameters were calculated in the same manner as they were previously and all variables defined in Table 6 remained the same.

The inhalation intake due solely to background concentration levels, as well as the total inhalation intake resulting from exposure to both the background and degreaser breathing zone concentration levels were modeled with the results presented in Tables 11 and 12. The annual TWA exposure and the LCR resulting from exposure to



both the background and degreaser breathing zone concentration levels were also modeled and are presented in Tables 13 and 14.

**Table 11. Summary Statistics for Simulation of TCE Intake at Various Distances Resulting From Background Concentration Levels Only.**

| Parameter         | Inhalation Intake Resulting From Background Concentrations |      |      |      |      |
|-------------------|--|------|------|------|------|
| Distribution      | Normal   |      |      |      |      |
| Units             | (m <sup>3</sup> /day)                                      |      |      |      |      |
| Distance (feet)   | 10   | 20   | 30   | 40   | 50   |
| Minimum=          | 0.31   | 0.09 | 0.04 | 0.02 | 0.01 |
| Maximum=          | 16.46  | 4.99 | 1.99 | 1    | 0.5  |
| Mean=             | 5.6  | 1.7  | 0.68 | 0.34 | 0.17 |
| Std Deviation=    | 3.18   | 0.96 | 0.39 | 0.19 | 0.1  |
| Variance=         | 10.14  | 0.93 | 0.15 | 0.04 | 0.01 |
| Skewness=         | 0.34   | 0.34 | 0.34 | 0.34 | 0.34 |
| Kurtosis=         | 2.38   | 2.38 | 2.38 | 2.38 | 2.38 |
| Percentile Values |  |      |      |      |      |
| 5Perc=            | 0.94   | 0.28 | 0.11 | 0.06 | 0.03 |
| 10Perc=           | 1.42   | 0.43 | 0.17 | 0.09 | 0.04 |
| 15Perc=           | 1.91   | 0.58 | 0.23 | 0.12 | 0.06 |
| 20Perc=           | 2.46   | 0.74 | 0.3  | 0.15 | 0.07 |
| 25Perc=           | 3  | 0.91 | 0.36 | 0.18 | 0.09 |
| 30Perc=           | 3.5  | 1.06 | 0.42 | 0.21 | 0.11 |
| 35Perc=           | 4.01   | 1.21 | 0.49 | 0.24 | 0.12 |
| 40Perc=           | 4.5  | 1.36 | 0.54 | 0.27 | 0.14 |
| 45Perc=           | 4.92   | 1.49 | 0.6  | 0.3  | 0.15 |
| 50Perc=           | 5.39   | 1.63 | 0.65 | 0.33 | 0.16 |
| 55Perc=           | 5.91   | 1.79 | 0.72 | 0.36 | 0.18 |
| 60Perc=           | 6.32   | 1.92 | 0.77 | 0.38 | 0.19 |
| 65Perc=           | 6.82   | 2.07 | 0.83 | 0.41 | 0.21 |
| 70Perc=           | 7.39   | 2.24 | 0.9  | 0.45 | 0.22 |
| 75Perc=           | 7.91   | 2.4  | 0.96 | 0.48 | 0.24 |
| 80Perc=           | 8.46   | 2.56 | 1.03 | 0.51 | 0.26 |
| 85Perc=           | 9.13   | 2.77 | 1.11 | 0.55 | 0.28 |
| 90Perc=           | 10.08  | 3.06 | 1.22 | 0.61 | 0.31 |
| 95Perc=           | 11.1   | 3.36 | 1.35 | 0.67 | 0.34 |

**Table 12. Summary Statistics for Simulation of Total TCE Intake at Various Distances Resulting From Both Background and Degreaser Breathing Zone Concentration Levels.**

| Parameter         | Total Inhalation Intake Resulting From Exposure to Both Background and Degreaser Concentration Levels |       |       |       |       |
|-------------------|---|-------|-------|-------|-------|
| Distribution      | Normal  |       |       |       |       |
| Units             | (m <sup>3</sup> /day)   |       |       |       |       |
| Distance (feet)   | 10  | 20    | 30    | 40    | 50    |
| Minimum=          | 0.46  | 0.14  | 0.06  | 0.03  | 0.02  |
| Maximum=          | 77.69   | 66.22 | 63.23 | 62.23 | 61.73 |
| Mean=             | 12.41   | 8.51  | 7.49  | 7.15  | 6.98  |
| Std Deviation=    | 8.96  | 7.36  | 6.99  | 6.88  | 6.82  |
| Variance=         | 80.32   | 54.1  | 48.88 | 47.29 | 46.52 |
| Skewness=         | 1.35  | 1.77  | 1.89  | 1.93  | 1.94  |
| Kurtosis=         | 6.02  | 8.02  | 8.63  | 8.83  | 8.93  |
| Percentile Values |   |       |       |       |       |
| 5Perc=            | 1.76  | 0.93  | 0.64  | 0.53  | 0.46  |
| 10Perc=           | 2.65  | 1.47  | 1.06  | 0.89  | 0.82  |
| 15Perc=           | 3.64  | 1.98  | 1.47  | 1.24  | 1.13  |
| 20Perc=           | 4.67  | 2.48  | 1.86  | 1.65  | 1.56  |
| 25Perc=           | 5.63  | 3.13  | 2.37  | 2.09  | 1.99  |
| 30Perc=           | 6.64  | 3.82  | 2.96  | 2.69  | 2.55  |
| 35Perc=           | 7.71  | 4.45  | 3.62  | 3.31  | 3.17  |
| 40Perc=           | 8.65  | 5.23  | 4.22  | 3.93  | 3.74  |
| 45Perc=           | 9.68  | 5.85  | 4.88  | 4.52  | 4.37  |
| 50Perc=           | 10.77   | 6.5   | 5.48  | 5.1   | 4.93  |
| 55Perc=           | 11.76   | 7.27  | 6.09  | 5.7   | 5.52  |
| 60Perc=           | 12.78   | 8.04  | 6.78  | 6.44  | 6.29  |
| 65Perc=           | 13.86   | 9.01  | 7.79  | 7.35  | 7.14  |
| 70Perc=           | 15.2  | 10.07 | 8.87  | 8.47  | 8.27  |
| 75Perc=           | 16.82   | 11.54 | 10.24 | 9.78  | 9.57  |
| 80Perc=           | 18.7  | 13.42 | 12.05 | 11.59 | 11.35 |
| 85Perc=           | 21.4  | 15.67 | 14.24 | 13.87 | 13.64 |
| 90Perc=           | 24.85   | 18.84 | 17.41 | 16.89 | 16.64 |
| 95Perc=           | 29.1  | 22.51 | 20.94 | 20.33 | 20.04 |


**Table 13. Summary Statistics for Simulation of Annual TWA Exposure Due to Exposure to Both Background Concentrations at Various Distances and Degreaser Breathing Zone Concentrations.**

| Parameter         | Annual TWA Exposure Resulting From Exposure to Both Background and Degreaser Concentration Levels |        |        |        |        |
|-------------------|---|--------|--------|--------|--------|
| Distribution      | Normal  |        |        |        |        |
| Units             | (ppm)   |        |        |        |        |
| Distance (feet)   | 10  | 20     | 30     | 40     | 50     |
| Minimum=          | 20.31   | 6.67   | 2.87   | 1.51   | 0.77   |
| Maximum=          | 183.36  | 168.14 | 164.16 | 162.84 | 162.18 |
| Mean=             | 58.51   | 41.27  | 36.77  | 35.27  | 34.52  |
| Std Deviation=    | 22.19   | 22.93  | 23.15  | 23.22  | 23.26  |
| Variance=         | 492.31  | 525.96 | 535.78 | 539.15 | 540.85 |
| Skewness=         | 0.96  | 0.98   | 0.98   | 0.98   | 0.98   |
| Kurtosis=         | 4   | 3.98   | 3.96   | 3.96   | 3.96   |
| Percentile Values |   |        |        |        |        |
| 5Perc=            | 29.93   | 11.86  | 7.08   | 5.48   | 4.69   |
| 10Perc=           | 33.4  | 15.39  | 10.72  | 9.15   | 8.34   |
| 15Perc=           | 36.39   | 18.35  | 13.58  | 12.02  | 11.21  |
| 20Perc=           | 39  | 21.24  | 16.52  | 14.96  | 14.15  |
| 25Perc=           | 41.91   | 23.86  | 19.14  | 17.53  | 16.73  |
| 30Perc=           | 44.29   | 26.04  | 21.33  | 19.75  | 18.94  |
| 35Perc=           | 46.78   | 28.83  | 24.1   | 22.5   | 21.7   |
| 40Perc=           | 49.08   | 31.57  | 26.99  | 25.46  | 24.65  |
| 45Perc=           | 51.83   | 34.24  | 29.63  | 28.13  | 27.36  |
| 50Perc=           | 54.36   | 37.05  | 32.52  | 30.93  | 30.21  |
| 55Perc=           | 57.38   | 40.31  | 35.79  | 34.23  | 33.47  |
| 60Perc=           | 60.52   | 43.38  | 38.71  | 37.25  | 36.51  |
| 65Perc=           | 63.51   | 46.41  | 42.1   | 40.59  | 39.83  |
| 70Perc=           | 66.85   | 49.75  | 45.48  | 44.11  | 43.38  |
| 75Perc=           | 71.16   | 54.15  | 49.85  | 48.34  | 47.58  |
| 80Perc=           | 75.7  | 58.99  | 54.78  | 53.31  | 52.59  |
| 85Perc=           | 81.58   | 64.61  | 60.32  | 58.96  | 58.2   |
| 90Perc=           | 89.97   | 73.3   | 68.98  | 67.47  | 66.73  |
| 95Perc=           | 101.22  | 85.23  | 81.27  | 79.99  | 79.36  |


**Table 14. Summary Statistics for Simulation of Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at Various Distances and Degreaser Breathing Zone Concentrations.**

| Parameter         | Lifetime Cancer Risk Resulting From Exposure to Both Background and Degreaser Concentration Levels |      |      |      |      |
|-------------------|--|------|------|------|------|
| Distribution      | Normal   |      |      |      |      |
| Units             |  |      |      |      |      |
| Distance (feet)   | 10   | 20   | 30   | 40   | 50   |
| Minimum=          | 0.01   | 0    | 0    | 0    | 0    |
| Maximum=          | 1.32   | 1.13 | 1.07 | 1.06 | 1.05 |
| Mean=             | 0.21   | 0.14 | 0.13 | 0.12 | 0.12 |
| Std Deviation=    | 0.15   | 0.13 | 0.12 | 0.12 | 0.12 |
| Variance=         | 0.02   | 0.02 | 0.01 | 0.01 | 0.01 |
| Skewness=         | 1.35   | 1.77 | 1.89 | 1.93 | 1.94 |
| Kurtosis=         | 6.02   | 8.02 | 8.63 | 8.83 | 8.93 |
| Percentile Values |  |      |      |      |      |
| 5Perc=            | 0.03   | 0.02 | 0.01 | 0.01 | 0.01 |
| 10Perc=           | 0.05   | 0.03 | 0.02 | 0.02 | 0.01 |
| 15Perc=           | 0.06   | 0.03 | 0.03 | 0.02 | 0.02 |
| 20Perc=           | 0.08   | 0.04 | 0.03 | 0.03 | 0.03 |
| 25Perc=           | 0.1  | 0.05 | 0.04 | 0.04 | 0.03 |
| 30Perc=           | 0.11   | 0.06 | 0.05 | 0.05 | 0.04 |
| 35Perc=           | 0.13   | 0.08 | 0.06 | 0.06 | 0.05 |
| 40Perc=           | 0.15   | 0.09 | 0.07 | 0.07 | 0.06 |
| 45Perc=           | 0.16   | 0.1  | 0.08 | 0.08 | 0.07 |
| 50Perc=           | 0.18   | 0.11 | 0.09 | 0.09 | 0.08 |
| 55Perc=           | 0.2  | 0.12 | 0.1  | 0.1  | 0.09 |
| 60Perc=           | 0.22   | 0.14 | 0.12 | 0.11 | 0.11 |
| 65Perc=           | 0.24   | 0.15 | 0.13 | 0.12 | 0.12 |
| 70Perc=           | 0.26   | 0.17 | 0.15 | 0.14 | 0.14 |
| 75Perc=           | 0.29   | 0.2  | 0.17 | 0.17 | 0.16 |
| 80Perc=           | 0.32   | 0.23 | 0.2  | 0.2  | 0.19 |
| 85Perc=           | 0.36   | 0.27 | 0.24 | 0.24 | 0.23 |
| 90Perc=           | 0.42   | 0.32 | 0.3  | 0.29 | 0.28 |
| 95Perc=           | 0.49   | 0.38 | 0.36 | 0.35 | 0.34 |


The distances at which workers performed their primary job of assembling, testing, or tearing-down aircraft parts ranged between approximately 20 and 60 feet. These are the distances at which they would have been exposed to the background concentrations caused by nearby degreasers. At these distances, the model results indicate that the exposure to background levels is relatively insignificant when compared with the exposure obtained from performing vapor degreasing operations. For comparison purposes, graphs of the LCR resulting from both exposures are presented in Figures 17 through 21.




**Figure 17. Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 10 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations.**




**Figure 18. Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 20 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations.**



**Figure 19. Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 30 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations.**



**Figure 20. Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 40 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations.**



**Figure 21. Lifetime Cancer Risk Due to Exposure to Both Background Concentrations at a Distance of 50 Feet From an Idle Tank and Degreaser Breathing Zone Concentrations.**

## ***V. Conclusion***

The purpose of this research was to determine whether it was possible to quantitatively determine the exposure to trichloroethylene by aircraft workers employed at Hill Air Force Base, Ogden, Utah from 1955 through 1979. The interest in this particular cohort was due to an epidemiology study performed by Dr. R. Spirtas of the National Cancer Institute on the same cohort. One of the findings of the study was there existed no overall association between exposure to TCE and mortality. By better quantifying the exposures experienced by the cohort, an additional measure of validity could be applied to the study and its results. Consequently, there would be an addition to the weight of epidemiological evidence either supporting or refuting the current classification of TCE as a probable human carcinogen.

In order to determine the feasibility of modeling the exposure in question, it was necessary to visit Hill Air Force Base. Historical documents including photographs, industrial hygiene surveys, clinical records, shop drawings, and monitoring results were reviewed. Additionally, site surveys of existing facilities and conversations with current employees were made. Analysis of this information leads to the conclusion that the primary exposures to TCE at Hill AFB occurred as a result of vapor degreasing operations or its use as a cold state solvent for spot cleaning. Spot cleaning was performed primarily on benchtops on electrical, optical, and other components removed from the aircraft. It was also performed inside various sections of the aircraft such as the wings to clean fuel lines, electrical conductors, hydraulic lines, etc. Vapor degreasing was performed throughout the base in shops which overhauled major



components of the aircraft such as the struts, wheels, and brakes. The exposures experienced as a result of spot cleaning with cold state solvents were not monitored or recorded until the late 1970's. However, TCE had been replaced by trichloroethane as a cold state solvent in 1968. Conversely, results from monitoring of TCE vapor degreasers existed beginning in the mid to late 1960's. Until the late 1970's, monitoring efforts had been infrequent. The Struts shop and the Wheels and Brakes shops seemed to be the focus of vapor degreaser monitoring operations. As a result, data primarily pertaining to these shops was used to estimate the exposures which occurred over the study period.

Two methods were used to estimate the exposure of workers who performed vapor degreaser activities, Monte Carlo simulation and multi-point diffusion modeling. Monte Carlo simulation was used in an effort to account for some of the many uncertainties associated with estimating a historical exposure, especially when limited data is available. This method produces a more realistic representation of the actual ranges of exposure. The second method consisted of using monitoring data to estimate the steady-state emission rate of the degreasers. Using those calculated emission rates, concentrations at other locations within the work area were estimated.

The 50th and 95th percentile annual 8 hour TWA exposure levels for workers performing degreasing operations were 15 ppm and 57 ppm, respectively. Breathing zone concentrations while performing vapor degreasing operations ranged from 0 ppm to 620 ppm. The median value was 180 ppm and the mean was 210 ppm. Using the multi-point diffusion model, concentrations within 50 feet of the vapor degreaser were

estimated. The mean concentration at 10 feet was estimated at 56 ppm. At 20 feet the mean concentration was estimated to be 20 ppm. For a person working at a distance of 20 feet from an idle degreaser for six hours per day, with the remaining two hours spent cleaning parts at the vapor degreaser, the 8 hour TWA for this worker would be 41 ppm.

To put these estimates into perspective they should be compared with the regulatory guidelines. Through 1977 the threshold limit value (TLV) for TCE was 100 ppm. In 1982 it was lowered to 50 ppm. The OSHA permissible exposure levels (PEL) for TCE during this time were as follows:

100 ppm - 8 hour TWA

200 ppm - ceiling (5 minutes in any 2 hours)

300 ppm - peak

The 55th percentile of the vapor degreaser breathing zone data corresponds to the 200 ppm ceiling value. The 70th percentile value corresponds to the 300 ppm peak concentration level.

Model estimates indicate that the OSHA ceiling and peak limits were probably exceeded only slightly less often than they were adhered to. The 95th percentile of the annual 8 hour TWA is approximately half the OSHA 8 hour TWA. When the estimated background concentrations were factored into the TWA exposure, the majority of workers still did not exceed the OSHA limit. This occurred because the exposure due to background concentrations was relatively insignificant when compared to the exposure experienced during degreasing operations.

Lifetime cancer risks were calculated using the modeled exposures. The results indicate that the chances of a worker who performed vapor degreasing operations experiencing some form of cancer are one in ten. With a lifetime cancer risk of 0.1, one would have expected the incidences of cancer found by Spirtas et al. to have been much greater. The expected risks are factors of 3 to 5 times greater than the acceptable risks usually associated with occupational and residential exposure which are 1 in 10,000 and 1 in 1,000,000 respectively. Both occupational and residential exposure guidelines are established based on risks of this magnitude. The exposure of the workers were within the established regulatory guidelines which were designed to ensure those acceptable risk levels were not exceeded. The large difference between the expected cancer risk and the observed risk, coupled with the fact that the the MCL for TCE is approximately a factor of 2 smaller than the exposure levels experienced by the workers suggests that the MCL could be increased by at least a factor of 1 without exceeding already acceptable risk levels.

The major assumption of this research was that the monitoring data which was taken primarily from 1968-1979 was representative of the entire study period, 1955-1979. The assumption was made based on having analyzed the available data and concluding the major factors affecting concentration levels remained relatively consistent throughout the entire period. A study of 80 workers employed in 24 workshops belonging to 10 different factories of the Swiss mechanical engineering industry was performed in 1954 to determine the effects of exposure to trichloroethylene. All factories used trichloroethylene in both open and closed tank

heated vapor degreasers. Factory average concentrations near the open tank degreasers ranged from 20 ppm to 325 ppm. The high end of this range was due to workers who ignored safety procedures and allowed parts to drip outside the tank. In the center of the workshop the resulting concentrations varied from 0 ppm to 225 ppm. This maximum was from the same factory and workshop as above. Concentrations near closed tanks varied from 11 ppm to 56 ppm. In the center of the workshop the resulting concentrations were all 0 ppm except for one factory where it was 35 ppm (Grandjean et al., 1955:131-133). The similarities of the concentrations measured in the Grandjean study with those found at Hill suggest that practices of that time were not that different than they were through the 1970's at Hill, thus supporting the major assumption of this research.

## **Appendix A: Tables**

**Table A.1 SMR's (Standardised Mortality Ratio's) for selected causes of death among white males by cumulative exposure to trichloroethylene (TCE) (Spiras et al, 1990:46).**

| Cause of Death           | < 5 years | 5-25 years | >25 years | Total Exposure | Chi For Trend (1) |
|--------------------------|-----------|------------|-----------|----------------|-------------------|
| All Causes SMR           | 87**      | 88**       | 99        | 92*            | 2.48*             |
| Observed/Expected        | 562/649.2 | 341/386.3  | 612/612.3 | 1508/1647.8    |                   |
| All Cancer               | 94        | 87         | 94        | 92             | 0.12              |
|                          | 99/105.6  | 56/64.1    | 93/98.8   | 248/268.4      |                   |
| Buccal/Pharynx           | 88        | -          | 142       | 88             | 0.64              |
|                          | 0.87      | 0          | 1.43      | 0.88           |                   |
| Biliary Passages (2)     | 200       | 500*       | 106       | 236            | -0.67             |
|                          | 2/1.0     | 5          | 1/1.0     | 2.4            |                   |
| Primary Liver Cancer (2) | 324       | -          | -         | 127            | (3)               |
|                          | 3.33      | 0          | 0         | 1.25           |                   |
| Pancreas                 | 90        | 75         | 81        | 83             | -0.18             |
|                          | 0.9       | 3/4.0      | 0.81      | 0.83           |                   |
| Lung                     | 96        | 88         | 107       | 98             | 0.42              |
|                          | 25/26.0   | 0.88       | 1.07      | 0.98           |                   |
| Prostate                 | 68        | 48         | 109       | 80             | 1.12              |
|                          | 0.68      | 0.48       | 12/11.0   | 0.8            |                   |
| Testes                   | 119       | -          | -         | 50             | (3)               |
|                          | 1.25      | 0          | 0         | 0.5            |                   |
| Kidney                   | 191       | -          | 124       | 120            | -0.57             |
|                          | 1.92      | 0          | 1.25      | 1.19           |                   |
| Bladder                  | 142       | 177        | 107       | 136            | -0.38             |
|                          | 1.43      | 1.76       | 1.07      | 1.37           |                   |
| CNS                      | 73        | 163        | 57        | 89             | -0.19             |
|                          | 0.73      | 1.6        | 0.57      | 0.89           |                   |
| All Lymph + Hemato.      | 73        | 61         | 119       | 87             | 1.26              |
|                          | 0.72      | 0.6        | 1.19      | 0.87           |                   |
| Leukemia                 | 58        | -          | 124       | 68             | 1.34              |
|                          | 0.58      | 0          | 1.25      | 0.69           |                   |
| Multiple Myeloma (2)     | 114       | 95         | 119       | 111            | 0.03              |
|                          | 1.11      | 0.91       | 1.18      | 1.11           |                   |

| Cause of Death   | < 5 years | 5-25 years | >25 years | Total Exposure | Chi For Trend (1) |
|--|-----------|------------|-----------|----------------|-------------------|
| Non-Hodgkin's Lymph. (2)   | 128       | 129        | 57        | 102            | -0.91             |
|  | 1.28      | 1.3        | 0.57      | 1.02           |                   |
| Ischemic HD  | 94        | 94         | 105       | 98             | 1.12              |
|  | 0.94      | 0.94       | 1.05      | 0.98           |                   |
| Emphysema  | 31**      | 90         | 131       | 83             | 2.82*             |
|  | 0.31      | 0.88       | 1.32      | 0.83           |                   |
| Asthma   | 129       | 423        | 250       | 244            | 0.33              |
|  | 1.25      | 4          | 2.5       | 5/2.0          |                   |
| Cirrhosis of Liver   | 47*       | 55         | 105       | 69             | 1.82              |
|  | 0.47      | 0.55       | 1.06      | 0.69           |                   |
| Nephritis  | 58        | 102        | 126       | 93             | 0.88              |
|  | 0.59      | 2/2.0      | 1.25      | 0.93           |                   |
| <p>* Significant at 5% Level</p> <p>(1) Derived from Chi-square test for linear trend (Breslow et al., 1983)</p> <p>(2) Special categories created for this study</p> <p>(3) Chi not computed if number of observed deaths &lt; 5</p> <p>Note:</p> <p>1. Cumulative exposure categories were derived by cumulatively multiplying the exposure index assigned to each job by time exposed at that level. See Stewart et al. for a detailed explanation of the derivation.</p> |           |            |           |                |                   |

**Table A.2 SMR's for selected causes of death among white females by cumulative exposure to trichlorethylene (TCE) (Spirtas et al., 1990: 47).**

| Cause of Death           | < 5 years | 5-25 years | >25 years | Total Exposure | Chi For Trend (1) |
|--------------------------|-----------|------------|-----------|----------------|-------------------|
| All Causes SMR           | 78        | 60*        | 87        | 82*            | 0.9               |
| Observed/Expected        | 35/44.7   | 18/29.9    | 133/152.5 | 186/227.2      |                   |
| All Cancer               | 88        | 43         | 64        | 67*            | -2.94*            |
|                          | 10/11.4   | 3/7.0      | 20/31.1   | 33/49.4        |                   |
| Buccal/Pharynx           | -         | -          | -         | -              | (3)               |
|                          | 0/0.1     | 0/0.1      | 0/0.4     | 0/0.6          |                   |
| Biliary Passages (2)     | 435       | -          | 143       | 167            | (3)               |
|                          | 1/0.2     | 0/0.2      | 1/0.7     | 2/1.2          |                   |
| Primary Liver Cancer (2) | -         | -          | -         | -              | (3)               |
|                          | 0/0.0     | 0/0.0      | 0/0.1     | 0/0.2          |                   |
| Pancreas                 | -         | -          | 125       | 81             | (3)               |
|                          | 0/0.5     | 0/0.3      | 2/1.6     | 2/2.5          |                   |
| Lung                     | -         | -          | -         | -              | (3)               |
|                          | 0/0.7     | 0/0.4      | 0/1.7     | 0/2.8          |                   |
| Breast                   | 106       | 119        | 57        | 78             | -0.89             |
|                          | 3/2.8     | 2/1.7      | 4/7.0     | 9/11.5         |                   |
| Kidney                   | -         | -          | -         | -              | (3)               |
|                          | 0/0.2     | 0/0.1      | 0/0.5     | 0/0.8          |                   |
| Bladder                  | -         | -          | 265       | 183            | (3)               |
|                          | 0/0.1     | 0/0.1      | 1/0.4     | 1/0.6          |                   |
| CNS                      | -         | -          | -         | -              | (3)               |
|                          | 0/0.4     | 0/0.2      | 0/0.8     | 0/1.4          |                   |
| All Lymph + Hemato.      | 277       | -          | 125       | 143            | -0.93             |
|                          | 3/1.1     | 0/0.7      | 4/3.1     | 7/4.8          |                   |
| Leukemia                 | 240       | -          | 82        | 106            | (3)               |
|                          | 1/0.4     | 0/0.3      | 1/1.2     | 2/1.9          |                   |
| Multiple Myeloma (2)     | 602       | -          | -         | 130            | (3)               |
|                          | 1/0.2     | 0/0.1      | 0/0.5     | 1/0.8          |                   |



| Cause of Death   | < 5 years | 5-25 years | >25 years | Total Exposure | Chi For Trend (1) |
|--|-----------|------------|-----------|----------------|-------------------|
| Non-Hodgkin's Lymph. (2)   | 328       | -          | 330       | 286            | 0.2               |
|  | 1/0.3     | 0/0.2      | 3/0.9     | 4/1.4          |                   |
| Ischemic HD  | 106       | 13*        | 99        | 90             | 0.43              |
|  | 1/10.3    | 1/7.5      | 42/42.4   | 54/60.2        |                   |
| Emphysema  | -         | -          | 314       | 198            | (3)               |
|  | 0/0.2     | 0/0.1      | 2/0.6     | 2/1.0          |                   |
| Asthma   | -         | -          | -         | -              | (3)               |
|  | 0/0.1     | 0/0.1      | 0/0.3     | 0/0.5          |                   |
| Cirrhosis of Liver   | 326       | -          | -         | 88             | (3)               |
|  | 3/0.9     | 0/0.5      | 0/2.0     | 3/3.4          |                   |
| Nephritis  | -         | -          | 114       | 76             | (3)               |
|  | 0/0.3     | 0/0.2      | 1/0.9     | 1/1.3          |                   |
| <p>* Significant at 5% Level</p> <p>(1) Derived from Chi-square test for linear trend (Breslow et al., 1983)</p> <p>(2) Special categories created for this study</p> <p>(3) Chi not computed if number of observed deaths &lt; 5</p> <p>Note:</p> <p>1. Cumulative exposure categories were derived by cumulatively multiplying the exposure index assigned to each job by time exposed at that level. See Stewart et al. for a detailed explanation of the derivation.</p> |           |            |           |                |                   |

**Table A.3 Cause-Specific SMRs and confidence intervals adjusted for age and calender period of white males exposed to trichloroethylene (TCE) (Spirtas et al., 1990:44).**

| CAUSE OF DEATH                           | OBS   | EXP     | SMR (1) | 95% CI Limits |       |
|--|-------|---------|---------|---------------|-------|
|  |       |         |         | Lower         | Upper |
| All Causes of Death                      | 1,508 | 1,647.8 | 92**    | 87            | 96    |
| Tuberculosis                             | 0     | 3.7     | 0*      | 0             | 99    |
| All Malignant Neoplasms                  | 248   | 268.5   | 92      | 81            | 105   |
| Cancer of Buccal Cavity & Pharynx        | 5     | 5.7     | 88      | 29            | 206   |
| Cancer of Digestive Organs & Peritoneum  | 74    | 74.7    | 99      | 78            | 124   |
| Cancer of Esophagus                      | 6     | 5.7     | 106     | 39            | 230   |
| Cancer of Stomach                        | 14    | 16      | 88      | 48            | 147   |
| Cancer of Large Intestine                | 27    | 23.3    | 112     | 73            | 164   |
| Cancer of Rectum                         | 4     | 6.3     | 64      | 17            | 163   |
| Cancer of Biliary Passages & Liver       | 8     | 4.1     | 196     | 85            | 386   |
| Biliary Passages (2)                     | 6     | 2.5     | 238     | 87            | 519   |
| Liver, Primary (2)                       | 2     | 1.6     | ---     | ---           | ---   |
| Cancer of Pancreas                       | 14    | 16.9    | 83      | 45            | 139   |
| Cancer of All Other Digestive Organs     | 2     | 2.8     | 72      | 9             | 260   |
| Cancer of Respiratory System             | 65    | 69.5    | 94      | 72            | 119   |
| Cancer of Larynx                         | 1     | 2.9     | 34      | 1             | 191   |
| Cancer of Bronchus, Trachea, Lung        | 64    | 65.1    | 98      | 76            | 126   |
| Cancer of All Other Respiratory          | 0     | 1.4     | ---     | ---           | ---   |
| Cancer of Breast                         | 0     | 0.4     | ---     | ---           | ---   |
| All Uterine Cancers (Females Only)       | ---   | ---     | ---     | ---           | ---   |
| Cancer of Cervix Uteri (Females Only)    | ---   | ---     | ---     | ---           | ---   |
| Cancer of Other Female Genital Organs    | ---   | ---     | ---     | ---           | ---   |
| Cancer of Prostate (Males Only)          | 22    | 27.6    | 80      | 50            | 121   |
| Cancer of Testes and Other Male Genital  | 1     | 2       | ---     | ---           | ---   |
| Cancer of Kidney & Other Urinary Organs  | 8     | 6.7     | 120     | 52            | 237   |
| Cancer of Bladder                        | 10    | 7.3     | 137     | 65            | 251   |
| Malignant Melanoma of Skin               | 5     | 5.2     | 96      | 31            | 224   |
| Cancer of Eye                            | 0     | 0.5     | ---     | ---           | ---   |
| Cancer of Central Nervous System         | 9     | 10.1    | 89      | 41            | 170   |
| Cancer of Thyroid Gland & Other Endocrin | 1     | 1.5     | ---     | ---           | ---   |
| Cancer of Bone                           | 3     | 1.1     | 263     | 54            | 767   |
| Cancer of All Lymphatic & Haematopoietic | 30    | 34.6    | 87      | 59            | 124   |

| CAUSE OF DEATH                              | OBS | EXP   | SMR (1) | 95% CI Limits |       |
|---|-----|-------|---------|---------------|-------|
|   |     |       |         | Lower         | Upper |
| Lymphosarcoma & Reticulosarcoma             | 9   | 8     | 112     | 51            | 213   |
| Hodgkin's Disease                           | 4   | 4.3   | 93      | 25            | 237   |
| Leukemia & Aleukemia                        | 9   | 13.1  | 69      | 31            | 130   |
| Cancer of All Other Lymphopoietic Tissue    | 8   | 9.2   | 87      | 38            | 172   |
| Multiple Myeloma (2)                        | 5   | 4.5   | 111     | 36            | 259   |
| Non-Hodgkin's Lymphoma (2)                  | 10  | 9.8   | 103     | 49            | 189   |
| All Other Malignant Neoplasms               | 15  | 21.2  | 71      | 40            | 117   |
| Benign Neoplasms                            | 5   | 4.3   | 117     | 38            | 273   |
| Diabetes Mellitus                           | 26  | 27.6  | 94      | 62            | 138   |
| Cerebrovascular Disease                     | 84  | 101   | 83      | 66            | 103   |
| All Heart Disease                           | 618 | 640.6 | 97      | 89            | 104   |
| Rheumatic Heart Disease                     | 34  | 33.4  | 102     | 71            | 142   |
| Ischemic Heart Disease                      | 551 | 561.7 | 98      | 90            | 107   |
| Chronic Disease of Endocard.; Other Myocard | 3   | 8     | 37      | 8             | 109   |
| Hypertension with Heart Disease             | 5   | 6.8   | 73      | 24            | 171   |
| All other Heart Disease                     | 25  | 43    | 58**    | 38            | 86    |
| Hypertension w/o Heart Disease              | 1   | 3.7   | 27      | 1             | 149   |
| Non-malignant Respiratory Disease           | 106 | 118.3 | 88      | 72            | 107   |
| Influenza & Pneumonia                       | 28  | 39.5  | 68*     | 45            | 100   |
| Bronchitis, Emphysema, Asthma               | 40  | 43.6  | 92      | 66            | 125   |
| Bronchitis                                  | 7   | 8.4   | 84      | 34            | 172   |
| Emphysema                                   | 28  | 33.6  | 83      | 55            | 121   |
| Asthma                                      | 5   | 2.1   | 244     | 79            | 570   |
| Other Non-malignant Respiratory Disease     | 37  | 36.9  | 100     | 71            | 138   |
| Ulcer of Stomach & Duodenum                 | 10  | 10.9  | 92      | 44            | 169   |
| Cirrhosis of Liver                          | 25  | 36.3  | 69      | 45            | 102   |
| Nephritis & Nephrosis                       | 8   | 8.6   | 93      | 40            | 184   |

| CAUSE OF DEATH   | OBS | EXP   | SMR (1) | 95% CI Limits |       |
|--|-----|-------|---------|---------------|-------|
|  |     |       |         | Lower         | Upper |
| All External Causes of Death   | 128 | 205.6 | 62**    | 52            | 74    |
| Accidents  | 79  | 141.1 | 56**    | 44            | 70    |
| Motor Vehicle Accidents  | 33  | 61.2  | 54**    | 37            | 76    |
| All Other Accidents  | 46  | 79.7  | 58**    | 42            | 77    |
| Suicides   | 41  | 45.5  | 90      | 65            | 122   |
| Homicides & Other External Causes  | 8   | 10    | 80      | 35            | 158   |
| All Other Causes of Death  | 161 | 216.5 | 74**    | 63            | 87    |
| Unknown Causes (999.9)   | 93  |       |         |               |       |
| <p>* Significant at 5% Level</p> <p>** Significant at 1% Level</p> <p>(1) SMR's and CI's presented only if number of observed or expected deaths &gt; 2</p> <p>(2) Special categories created for this study</p> |     |       |         |               |       |

**Table A.4 Cause-Specific SMRs and confidence intervals adjusted for age and calender period of white females exposed to trichloroethylene (TCE) (Spirtas et al., 1990:45).**

| CAUSE OF DEATH                           | OBS | EXP   | SMR (1) | 95% CI Limits |       |
|--|-----|-------|---------|---------------|-------|
|  |     |       |         | Lower         | Upper |
| All Causes of Death                      | 186 | 227.2 | 82**    | 71            | 95    |
| Tuberculosis                             | 0   | 0.2   | ---     | ---           | ---   |
| All Malignant Neoplasms                  | 33  | 49.4  | 67*     | 46            | 94    |
| Cancer of Buccal Cavity & Pharynx        | 0   | 0.6   | ---     | ---           | ---   |
| Cancer of Digestive Organs & Peritoneum  | 7   | 13    | 54      | 22            | 111   |
| Cancer of Esophagus                      | 0   | 0.2   | ---     | ---           | ---   |
| Cancer of Stomach                        | 0   | 2     | ---     | ---           | ---   |
| Cancer of Large Intestine                | 2   | 5.5   | 37      | 4             | 132   |
| Cancer of Rectum                         | 1   | 1.1   | ---     | ---           | ---   |
| Cancer of Biliary Passages & Liver       | 2   | 1.2   | ---     | ---           | ---   |
| Biliary Passages (2)                     | 2   | 1.1   | ---     | ---           | ---   |
| Liver, Primary (2)                       | 0   | 0.2   | ---     | ---           | ---   |
| Cancer of Pancreas                       | 2   | 2.5   | 81      | 10            | 291   |
| Cancer of All Other Digestive Organs     | 0   | 0.5   | ---     | ---           | ---   |
| Cancer of Respiratory System             | 0   | 3.1   | 0       | 0             | 121   |
| Cancer of Larynx                         | 0   | 0.1   | ---     | ---           | ---   |
| Cancer of Bronchus, Trachea, Lung        | 0   | 2.8   | 0       | 0             | 131   |
| Cancer of All Other Respiratory          | 0   | 0.2   | ---     | ---           | ---   |
| Cancer of Breast                         | 9   | 11.5  | 79      | 36            | 149   |
| All Uterine Cancers (Females Only)       | 4   | 4.1   | 98      | 27            | 251   |
| Cancer of Cervix Uteri (Females Only)    | 4   | 1.8   | 224     | 61            | 574   |
| Cancer of Other Female Genital Organs    | 4   | 4     | 100     | 27            | 255   |
| Cancer of Prostate (Males Only)          | -   | ---   | ---     | ---           | ---   |
| Cancer of Testes and Other Male Genital  | -   | ---   | ---     | ---           | ---   |
| Cancer of Kidney & Other Urinary Organs  | 0   | 0.8   | ---     | ---           | ---   |
| Cancer of Bladder                        | 1   | 0.6   | ---     | ---           | ---   |
| Malignant Melanoma of Skin               | 1   | 0.6   | ---     | ---           | ---   |
| Cancer of Eye                            | 0   | 0.1   | ---     | ---           | ---   |
| Cancer of Central Nervous System         | 0   | 1.4   | ---     | ---           | ---   |
| Cancer of Thyroid Gland & Other Endocrin | 0   | 0.4   | ---     | ---           | ---   |
| Cancer of Bone                           | 0   | 0.1   | ---     | ---           | ---   |
| Cancer of All Lymphatic & Haematopoietic | 7   | 4.9   | 143     | 58            | 295   |

| CAUSE OF DEATH                              | OBS | EXP  | SMR (1) | 95% CI Limits |       |
|---|-----|------|---------|---------------|-------|
|   |     |      |         | Lower         | Upper |
| Lymphosarcoma & Reticulosarcoma             | 3   | 1.2  | 261     | 54            | 761   |
| Hodgkin's Disease                           | 0   | 0.3  | --      | --            | --    |
| Leukemia & Aleukemia                        | 2   | 1.9  | --      | --            | --    |
| Cancer of All Other Lymphopoietic Tissue    | 2   | 1.5  | --      | --            | --    |
| Multiple Myeloma (2)                        | 1   | 0.8  | --      | --            | --    |
| Non-Hodgkin's Lymphoma (2)                  | 4   | 1.4  | 286     | 78            | 731   |
| All Other Malignant Neoplasms               | 0   | 4.2  | 0*      | 0             | 86    |
| Benign Neoplasms                            | 2   | 0.8  | --      | --            | --    |
| Diabetes Mellitus                           | 6   | 6.8  | 88      | 32            | 191   |
| Cerebrovascular Disease                     | 22  | 26.6 | 83      | 52            | 125   |
| All Heart Disease                           | 70  | 78.7 | 89      | 69            | 112   |
| Rheumatic Heart Disease                     | 8   | 8.6  | 93      | 40            | 184   |
| Ischemic Heart Disease                      | 54  | 60.2 | 90      | 67            | 117   |
| Chronic Disease of Endocard.; Other Myocard | 1   | 1.5  | --      | --            | --    |
| Hypertension with Heart Disease             | 1   | 2    | --      | --            | --    |
| All other Heart Disease                     | 6   | 7.4  | 82      | 30            | 178   |
| Hypertension w/o Heart Disease              | 0   | 0.7  | --      | --            | --    |
| Non-malignant Respiratory Disease           | 4   | 10.6 | 38*     | 10            | 97    |
| Influenza & Pneumonia                       | 0   | 6.3  | 0**     | 0             | 59    |
| Bronchitis, Emphysema, Asthma               | 2   | 2.1  | 95      | 12            | 343   |
| Bronchitis                                  | 0   | 0.5  | --      | --            | --    |
| Emphysema                                   | 2   | 1    | --      | --            | --    |
| Asthma                                      | 0   | 0.5  | --      | --            | --    |
| Other Non-malignant Respiratory Disease     | 2   | 2.5  | 80      | 10            | 287   |
| Ulcer of Stomach & Duodenum                 | 0   | 1.1  | --      | --            | --    |
| Cirrhosis of Liver                          | 3   | 3.4  | 88      | 18            | 257   |
| Nephritis & Nephrosis                       | 1   | 1.3  | --      | --            | --    |

| CAUSE OF DEATH   | OBS | EXP  | SMR (1) | 95% CI Limits |       |
|--|-----|------|---------|---------------|-------|
|  |     |      |         | Lower         | Upper |
| All External Causes of Death   | 9   | 13   | 69      | 32            | 131   |
| Accidents  | 7   | 9.8  | 71      | 29            | 147   |
| Motor Vehicle Accidents  | 5   | 4.7  | 106     | 34            | 247   |
| All Other Accidents  | 2   | 5.2  | 39      | 5             | 140   |
| Suicides   | 2   | 2    | 99      | 12            | 357   |
| Homicides & Other External Causes  | 0   | 0.7  | —       | —             | —     |
| All Other Causes of Death  | 17  | 34.2 | 50**    | 29            | 80    |
| Unknown Causes (999.9)   | 20  |      |         |               |       |
| <p>* Significant at 5% Level</p> <p>** Significant at 1% Level</p> <p>(1) SMR's and CI's presented only if number of observed or expected deaths &gt; 2</p> <p>(2) Special categories created for this study</p> |     |      |         |               |       |

**Table A.5 Recorded TCE Exposure Levels from Vapor Degreasing Activities**

| Date     | Building | Sample Location | Sample Duration (min) | Instrument Used | Conc. (ppm) | Remarks                                     |
|----------|----------|-----------------|-----------------------|-----------------|-------------|---|
| 09/22/65 | 264      | BZ              | NS                    | NS              | 100         | 20  |
| 05/18/68 | 264      | BZ              | NS                    | NS              | 100         | 32  |
| 05/18/68 | 264      | BZ              | NS                    | NS              | 250         | cold dip tank                               |
| 04/09/73 | 205      | BZ              | NS                    | NS              | 0.5         |   |
| 09/25/75 | 264      | BZ              | 60                    | Charcoal T.     | 145         |   |
| 11/03/75 | 510      | NS              | NS                    | Draeger T.      | 75          | 1' above edge of tank                       |
| 11/03/75 | 510      | NS              | NS                    | Draeger T.      | 75          | middle of tank                              |
| 04/12/76 | 265      | BZ              | NS                    | NS              | 300         |   |
| 04/27/76 | 205      | BZ              | NS                    | NS              | 5           |   |
| 08/16/76 | 264      | BZ              | NS                    | NS              | 500         | cross drafts, fans pulling vapors from tank |
| 08/16/76 | 264      | BZ              | NS                    | NS              | 400         | same as above, lid closed                   |
| 06/14/77 | 264      | NS              | NS                    | Draeger T.      | 100         |   |
| 12/21/77 | 205      | BZ              | NS                    | Draeger T.      | 500         | door to E. of machine opened -cross drafts  |
| 12/21/77 | 205      | BZ              | NS                    | Draeger T.      | 350         |   |
| 04/21/78 | 264      | BZ              | NS                    | NS              | 125         | during spray lance use                      |
| 04/21/78 | 264      | BG,7.5          | NS                    | NS              | 200         | during spray lance use                      |
| 04/26/78 | 264      | BZ              | NS                    | NS              | 450         | during spray lance use                      |
| 04/26/78 | 264      | BG,20           | NS                    | NS              | 45          | during spray lance use                      |
| 04/28/78 | 264      | BZ              | NS                    | NS              | 350         | during spray lance use                      |
| 04/28/78 | 264      | BG, NS          | NS                    | NS              | 0           | during lance spray use                      |
| 05/18/78 | 264      | BG,10           | NS                    | Draeger T.      | 0           |   |
| 05/18/78 | 264      | BZ              | NS                    | Draeger T.      | 75          |   |
| 09/07/78 | 264      | BZ              | NS                    | NS              | 0           | low while placing parts in VD               |
| 09/07/78 | 264      | BZ              | NS                    | NS              | 25          | low while removing parts from VD            |
| 09/07/78 | 264      | Source          | NS                    | NS              | 38          | source sample at breathing level of VD      |
| 09/07/78 | 264      | BZ              | NS                    | NS              | 132         | average while placing parts in VD           |
| 09/07/78 | 264      | BZ              | NS                    | NS              | 620         | peak while placing parts in VD              |



| Date     | Building | Sample Location | Sample Duration (min) | Instrument Used | Conc. (ppm) | Remarks                                 |
|----------|----------|-----------------|-----------------------|-----------------|-------------|---|
| 09/07/78 | 264      | BZ              | NS                    | NS              | 1,000       | peak while removing parts from VD       |
| 09/07/78 | 264      | BZ              | NS                    | NS              | 9           | from worker in magnaflux area           |
| 09/07/78 | 264      | BZ              | NS                    | NS              | 489         | average while removing parts from VD    |
| 09/25/78 | 510      | BZ              | 32                    | Charcoal T.     | 620         |   |
| 09/25/78 | 510      | BZ              | 30                    | Charcoal T.     | 470         |   |
| 10/01/78 | 264      | BZ              | NS                    | Miran IR        | 155         | lowering parts into vapor layer of VD   |
| 10/01/78 | 264      | BZ              | NS                    | Miran IR        | 200         | during spray lance use                  |
| 10/01/78 | 264      | BZ              | NS                    | Miran IR        | 100         | removing parts from VD @ 11 fpm         |
| 11/06/78 | 510      | BZ              | 255                   | Charcoal T.     | 29          |   |
| 11/06/78 | 510      | GRA             | 130                   | Charcoal T.     | 25          |   |
| 11/06/78 | 510      | GRA             | 233                   | Charcoal T.     | 12          |   |
| 11/06/78 | 510      | GRA             | 356                   | Charcoal T.     | 7           |   |
| 11/06/78 | 510      | BZ              | 132                   | Charcoal T.     | 54          |   |
| 01/05/79 | 510      | BG,2            | NS                    | Miran-1A        | 25          | after 4 strut pistons lowered into tank |
| 01/05/79 | 510      | BZ              | NS                    | Miran-1A        | 175         | after 4 strut pistons lowered into tank |
| 01/05/79 | 510      | BG, 2           | NS                    | Miran-1A        | 28          | during spray lance use                  |
| 01/05/79 | 510      | BZ              | NS                    | Miran-1A        | 300         | inst. limit, during spray lance use     |
| 01/05/79 | 510      | BZ              | NS                    | Miran-1A        | 270         | parts lowered into tank                 |
| 01/05/79 | 510      | BG,2            | NS                    | Miran-1A        | 36          | parts lowered into tank                 |
| 01/05/79 | 510      | BZ              | NS                    | Miran-1A        | 300         | inst. limit, during spray lance use     |
| 01/05/79 | 510      | BG, 2           | NS                    | Miran-1A        | 35          | During spray lance use                  |
| 01/05/79 | 510      | BZ              | NS                    | Miran-1A        | 300         | inst. limit, parts removed from tank    |
| 01/05/79 | 510      | BG, 2           | NS                    | Miran-1A        | 30          | parts removed from tank                 |
| 01/05/79 | 510      | BZ              | NS                    | Miran-1A        | 180         | Idle tank                               |
| 01/05/79 | 510      | BG, 2           | NS                    | Miran-1A        | 10          | idle tank                               |
| 01/05/79 | 510      | BG,2            | NS                    | Miran-1A        | 10          | inst. limit, idle tank, lid closed      |
| 01/05/79 | 510      | BG,2            | NS                    | Miran-1A        | 300         | inst. limit, tank lid opened rapidly    |
| 03/08/79 | 510      | BZ              | 25                    | NS              | 235         | 2' above tank while work performed      |

| Date     | Building | Sample Location | Sample Duration (min) | Instrument Used | Conc. (ppm) | Remarks                                     |
|----------|----------|-----------------|-----------------------|-----------------|-------------|---|
| 03/08/79 | 510      | NS              | 12                    | NS              | 25          | 6' above work platform while work performed |
| 03/08/79 | 510      | BZ              | 10                    | NS              | 200         | 2' above tank after work performed          |
| 03/08/79 | 510      | BG,15           | 15                    | NS              | 10          | average less than 10 ppm                    |
| 03/08/79 | 510      | BZ              | 20                    | NS              | 320         | '2 above grated area on tank                |
| 03/29/79 | 205      | BG,5            | NS                    | Miran-1A        | 35          | north side of tank                          |
| 03/29/79 | 264      | GRA             | 155                   | NS              | 11          |   |
| 03/29/79 | 205      | BZ              | NS                    | Miran-1A        | 285         | 2' above tank opening                       |
| 03/29/79 | 205      | BZ              | NS                    | Miran-1A        | 80          | 5' above tank opening                       |
| 03/29/79 | 205      | BG,25           | NS                    | Miran-1A        | 0           | north side of tank                          |
| 03/29/79 | 205      | BG,15           | NS                    | Miran-1A        | 0           | south side of tank                          |
| 03/29/79 | 205      | BG,5            | NS                    | Miran-1A        | 17          | front of tank                               |
| 03/29/79 | 264      | BZ              | 232                   | NS              | 33          |   |
| 03/29/79 | 264      | BZ              | 480                   | NS              | 13          |   |
| 03/29/79 | 205      | BG,10           | NS                    | Miran-1A        | 0           | 10' from front of tank                      |
| 03/29/79 | 205      | BG,5            | NS                    | Miran-1A        | 0           | south side of tank                          |
| 03/29/79 | 264      | BZ              | 110                   | NS              | 37          |   |
| 03/29/79 | 264      | BZ              | 140                   | NS              | 45          |   |
| 03/29/79 | 264      | BZ              | 205                   | NS              | 15          |   |
| 03/29/79 | 264      | BZ              | 145                   | NS              | 2           |   |
| 03/29/79 | 264      | BZ              | 120                   | NS              | 1           |   |

| Date  | Building | Sample Location | Sample Duration (min) | Instrument Used | Conc. (ppm) | Remarks         |
|---|----------|-----------------|-----------------------|-----------------|-------------|-----------------|
| 04/12/79  | 205      | BZ              | NS                    | NS              | 285         | 2' above tank   |
| 04/12/79  | 205      | GRA             | NS                    | NS              | 0           |                 |
| 04/12/79  | 205      | GRA             | NS                    | NS              | 0           |                 |
| 04/12/79  | 205      | GRA             | NS                    | NS              | 0           |                 |
| 04/12/79  | 205      | GRA             | NS                    | NS              | 0           |                 |
| 04/12/79  | 205      | GRA             | NS                    | NS              | 17          |                 |
| 04/12/79  | 205      | BZ              | NS                    | NS              | 80          | 5' above tank   |
| 12/21/79  | 205      | BZ              | NS                    | NS              | 350         | tank lid closed |
| 12/21/79  | 205      | BZ              | NS                    | NS              | 500         | tank lid open   |
| Notes:<br>1. Draeger T. - Draeger Pump and Collector Tube<br>2. Charcoal T. - Dupont Pump and Charcoal Tube<br>3. GRA - General Room Air<br>4. BG,xx - Background sample taken at xx lateral feet from nearest side of tank<br>5. NS - Not Specified<br>6. A blank remarks section indicates there was no additional information available describing the sample. |          |                 |                       |                 |             |                 |

## **Appendix B: Photographs**

Photo 1: Hill Air Force Base, B264 (side), date not available.



Photo 2: Hill Air Force Base, B264 (side), date not available.



Photo 3: Hill Air Force Base, B264 (front), date not available.



Photo 4: Hill Air Force Base, B264 (Aluminum parts cleaning line), date not available.



Photo 5: Hill Air Force Base, B205 (rear storage area), no date available.




Photo 6: Hill Air Force Base, B205 (parts cleaning line), no date available.





Photo 7: Hill Air Force Base, "Ron Baker dips a basket of parts in a degreaser.", 1977.





## ***Bibliography***

Allen, Bruce C. and Fisher, Jeffrey W. "Pharmacokinetic Modeling of Trichloroethylene and Trichloroacetic Acid in Humans." *Risk Analysis* 13, No. 1 (1993):71-86.

Bayer, Johan E., Lt Col et. al. "Report on Alleged Health Hazards in Building 100, Hill AFB, UT." Air Force/NIOSH Staff Assistance Team Report. Hill AFB, Utah, 1978.

Brown, Halina Szejnwald and Hattis, Dale. "The Role of Skin Absorption as a Route to Exposure to Volatile Organic Compounds in Household Tap Water: A Simulated Kinetic Approach." *Journal Of The American College Of Toxicology* 8, No. 12 (1989):839-851.

Callahan, Michael A. et al. *Water-Related Environmental Fate of 129 Priority Pollutants. Volume II. Halogenated Aliphatics.*

Cronin, William J. and Oswald, Eric J. "A Refinement of Risk Analysis Procedures For Trichloroethylene Through The Use Of The Monte Carlo Method In Conjunction With Physiologically Based Pharmacokinetic Modeling." Thesis. Air Force Institute of Technology 1993.

Droz, P.O., Wu, M.M., Cumberland, W.G., Berode, M. "Variability in Biological Monitoring of Solvent Exposure. I Development of a Population Physiological Model." *British Journal of Industrial Medicine* 46 (1989):447-460.

Enderby, G.E.H. "The Use and Abuse of Trichloroethylene." *British Medical Journal* 2 (1944): 300-302.

Esmen, Nurtan, Ph.D. "Retrospective Industrial Hygiene Surveys." *American Industrial Hygiene Association Journal* 40 (1979):58-65.

Feldman, Robert G., Mayer, Richard M., Taub, Arthur. "Evidence for Peripheral Neurotoxic Effect of Trichloroethylene." *Neurology* 20 (1970): 599-606.

Feldman, Robert G., Niles, Clyde, Proctor, Susan P., Jabre, Joseph. "Blink Reflex Measurement of Effects of Trichloroethylene Exposure on the Trigeminal Nerve." *Muscle & Nerve* 15 (1992):490-495.

Feldman, Robert G., White, Roberta Firnhaber, Currie, Jon N., Travers, Patricia Hyland, Lessell, Simmons. "Long-Term Follow-Up After Single Toxic Exposure to Trichloroethylene." *American Journal of Industrial Medicine* 8 (1985):119-126.

Feldman, Robert G. *Handbook of Clinical Neurology.* New York: North-Holland Publishing Co.,1979.

Fisher, Jeffrey W. "SERDP SAB, Thrust: Installation Restoration (IR-27), Title: Toxicology and Human Health Risks." Overview briefing of the SERDP SAB program prepared for the Occupational and Environmental Health Directorate, Toxicology Division. Wright-Patterson AFB, OH, May 19, 1993.

Franke, John E., Wadden, Richard A., and Scheff, Peter A. "Activity Based Emission Factors for Indoor Sources." *Proceedings of the 5th International Conference on Indoor Air Quality and Climate: Toronto, 29 July - 3 August 1990*. 765-770. Ottawa, Ontario: 1990.

Grandjean, E., Munchinger, R., Turrian, V., Haas, P.A., Knoepfel, H.K., Rosenmund, H. "Investigations into the Effects of Exposure to Trichloroethylene in Mechanical Engineering." *British Journal of Industrial Medicine* 12 (1955):131-142.

Hayes, R.S. "Estimating the Effect of Being Indoors on Total Exposure to Outdoor Air Pollution." *The Journal of the Air & Waste Management Association* 39, No. 11, (1989):1453-1461.

Howard, Phillip H., ed. *Handbook of Environmental Fate and Exposure Data For Organic Chemicals*. Chelsea, Michigan: Lewis Publishers, Inc., 1990.

Larson, J.L. and Bull, R.J. "Species Differences in the Metabolism of Trichloroethylene to the Carcinogenic Metabolites Trichloroacetate and Dichloroacetate." *Toxicology and Applied Pharmacology* 115 (1992):278-285.

Manahan, Stanley E. *Hazardous Waste Chemistry, Toxicology and Treatment*. Chelsea, Michigan: Lewis Publishers, Inc., 1990.

Masters, Gilbert M. *Introduction to Environmental Engineering and Science*. Englewood Cliffs, New Jersey: Prentice-Hall, Inc., 1991.

McKone, Thomas E. and Knezovich, John P. "The Transfer of Trichloroethylene (TCE) from a Shower to Indoor Air: Experimental Measurements and Their Implications." *Journal of the Air and Waste Management Association* 40 (1991):282-285.

Monson, Richard R., M.D., Sc.D. *Occupational Epidemiology, 2nd Edition*. Boca Raton, Florida: CRC Press, Inc., 1990.

National Institute for Occupational Safety and Health (NIOSH). *Criteria for a Recommended Standard...Occupational Exposure to Trichloroethylene*. U.S. Department of Health, Education, and Welfare, Public Health Service, 1973.

Pedelty, Joe F. and Holcomb, Larry C. "A Computer Simulation of Indoor Air Quality Which Models Changes in Point Sources and Ventilation." *Environmental Technology* 11 (1990):1053-1062.

Rao, Hari V. and Brown, David R. "A Physiologically Based Pharmacokinetic Assessment of Tetrachloroethylene in Groundwater for a Bathing and Showering Determination." *Risk Analysis* 13, No.1 (1993):37-49.

Royal Society of Chemistry. *Organo-Chlorine Solvents: Health Risks to Workers*. Brussels-Luxembourg: Staples Printers Rochester Ltd., 1986.

Smith, Thomas J., Hammond, Katherine S., Hallock, Marilyn, and Woskie, Susan R. "Exposure Assessment for Epidemiology: Characteristics of Exposure." *Applied Occupational Environmental Hygiene* 6, No. 6 (1991):441-447.

Spirtas, R., Stewart, P.A., Lee, J.S., Marano, D.E., Forbes, C.D., Grauman, D.J., Pettigrew, H.M., Blair, A., Hoover, R.N., Cohen, J.L. "Retrospective Cohort Mortality Study of Workers at an Aircraft Maintenance Facility. I. Epidemiological Results." *British Journal of Industrial Medicine* 48 (1991):515-530.

Spirtas, R. et al. "Retrospective Cohort Mortality Study of Workers at an Aircraft Maintenance Facility: II. Analysis by Selected Exposure Categories." Hill Mortality Study Final Report. Bethesda, Md., March 1, 1990.

Steinberg, Alfred D. and DeSesso, John M. "Have Animal Data Been Used Inappropriately to Estimate Risks to Humans from Environmental Trichloroethylene?" *Regulatory Toxicology and Pharmacology* 18 (1993):137-153.

Stewart, P.A., Lee, J.S., Marano, D.E., Spirtas, R., Forbes, C.D., Blair, A. "Retrospective Cohort Mortality Study of Workers at an Aircraft Maintenance Facility. II. Exposures and Their Assessment." *British Journal of Industrial Medicine* 48 (1991):531-537.

Stewart, Patricia Ann et al. "Estimating Historical Exposures to Formaldehyde in a Retrospective Mortality Study." *Applied Industrial Hygiene* 1, No. 1 (1986):34-41.

Thompson, Kimberly M., Burmaster, David E., and Crouch, Edmund A.C. "Monte Carlo Techniques for Quantitative Uncertainty Analysis in Public Health Risk Assessments." *Risk Analysis* 12, No. 1 (1992):53-63.

Wadden, Richard A., Scheff, Peter A., and Franke, John E. "Emission Factors for Trichloroethylene Vapor Degreasers." *American Industrial Hygiene Association Journal* 50, No. 9 (1989):496-500.

Whitmyre, Gary K. et al. "Human Exposure Assessment I: Understanding the Uncertainties." *Toxicology and Industrial Health* 8, No. 5 (1992):297-320.

Wilkes, Charles R. and Small, Mitchell J. "Inhalation Exposure Model For Volatile Chemicals From Indoor Uses of Water." *Atmospheric Environment* 26A, No.12 (1992):2227-2236.

Yu, Rong C. et al. "A Deterministic Mathematical Model for Quantitative Estimation of Historical Exposure." *American Industrial Hygiene Association Journal* 51, No. 4 (1990):194-201.

## *Vita*

Anthony O. Copeland was born 10 May 1967, at Duke University Medical Center in Durham, North Carolina. He spent the majority of his childhood in his grandmother's hometown of Warrenton, North Carolina. As a high school sophomore, he competed for and was selected to complete his junior and senior high school years at the North Carolina School of Science and Mathematics located also in Durham. Upon graduating, he attended North Carolina State University where he earned a Bachelor of Science Degree in Electrical Engineering. Commissioned as a Second Lieutenant in December 1989, he was assigned to the 14th Civil Engineering Squadron, Columbus Air Force Base, Mississippi. At Columbus AFB, he served as an electrical design and utility engineer from April 1990 to May 1992. His next assignment took him to Kunsan Air Base, Republic of Korea. While a member of the 8th Civil Engineering Squadron, he held the positions of Chief of Requirements and Chief of Maintenance Engineering. In June 1993, he entered the Graduate Engineering and Environmental Management Program at the Air Force Institute of Technology's School of Engineering.

| REPORT DOCUMENTATION PAGE  |  |   | Form Approved<br>OMB No. 0704-0188                                  |   |
|--|--|---|---|---|
| Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503  |  |   |   |   |
| 1. AGENCY USE ONLY (Leave blank)   |  | 2. REPORT DATE<br>September 1994                        |   | 3. REPORT TYPE AND DATES COVERED<br>Master's Thesis |
| 4. TITLE AND SUBTITLE<br>A RETROSPECTIVE QUANTITATIVE ASSESSMENT OF TRICHLOROETHYLENE EXPOSURE OF WORKERS AT AIRCRAFT MAINTENANCE FACILITIES AT HILL AIR FORCE BASE THROUGH THE USE OF MODELING  |  |   | 5. FUNDING NUMBERS  |   |
| 6. AUTHOR(S)<br><br>Anthony O. Copeland, Captain, USAF   |  |   |   |   |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)<br><br>Air Force Institute of Technology, WPAFB OH. 45433-6583  |  |   | 8. PERFORMING ORGANIZATION REPORT NUMBER<br><br>AFTT/GEE/ENV/94S-06 |   |
| 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)<br>Armstrong Laboratory, Toxicology Division<br>Wright-Patterson Air Force Base, OH 45433<br>Strategic Environmental Research and Development Program (SERDP)<br>for the Scientific Advisory Board: Thrust: Installation Restoration (IR-27)<br>Title: Toxicology and Human Health Risks   |  |   | 10. SPONSORING / MONITORING AGENCY REPORT NUMBER                    |   |
| 11. SUPPLEMENTARY NOTES  |  |   |   |   |
| 12a. DISTRIBUTION / AVAILABILITY STATEMENT<br>Approved for public release; distribution unlimited  |  |   | 12b. DISTRIBUTION CODE  |   |
| 13. ABSTRACT (Maximum 200 words)<br><br>Monte Carlo simulation and source-receptor modeling are used to estimate the TCE exposures encountered by select workers at aircraft maintenance facilities at Hill Air Force Base between 1955 and 1979. An epidemiological study of this group, a retrospective cohort study of 14,457 workers who were employed at the base for a minimum of one year between 1952 and 1956, was headed by Dr. R. Spirtas of the National Cancer Institute to evaluate mortality associated with occupational exposure. One of the major conclusions of the study was that TCE "probably does not pose a strong carcinogenic risk for man." In the Spirtas study, historic exposure levels were not quantitatively estimated. Instead, indices of exposure to TCE were assigned to reflect relative differences in exposure levels. It is the objective of this research effort to quantitatively estimate specific worker exposures, thus adding to the weight of evidence necessary to classify TCE as a human carcinogen or otherwise. |  |   |   |   |
| 14. SUBJECT TERMS<br>Exposure Assessment, Monte Carlo Simulation, Hill Air Force Base<br>Historical Exposure Estimation, Trichloroethylene, TCE, Computer Simulation<br>Multi-Point Diffusion Analysis, Occupational Exposure, Vapor Degreasers  |  |   | 15. NUMBER OF PAGES<br>101  |   |
|  |  |   | 16. PRICE CODE  |   |
| 17. SECURITY CLASSIFICATION OF REPORT<br>Unclassified  | 18. SECURITY CLASSIFICATION OF THIS PAGE<br>Unclassified | 19. SECURITY CLASSIFICATION OF ABSTRACT<br>Unclassified | 20. LIMITATION OF ABSTRACT<br>UL                                    |   |

## GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines to meet optical scanning requirements.**

### **Block 1. Agency Use Only (Leave Blank)**

**Block 2. Report Date.** Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

**Block 3. Type of Report and Dates Covered.** State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

**Block 4. Title and Subtitle.** A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

**Block 5. Funding Numbers.** To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

|                      |                              |
|----------------------|------------------------------|
| C - Contract         | PR - Project                 |
| G - Grant            | TA - Task                    |
| PE - Program Element | WU - Work Unit Accession No. |

**Block 6. Author(s).** Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

**Block 7. Performing Organization Name(s) and Address(es).** Self-explanatory.

**Block 8. Performing Organization Report Number.** Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

**Block 9. Sponsoring/Monitoring Agency Names(s) and Address(es).** Self-explanatory.

**Block 10. Sponsoring/Monitoring Agency Report Number.** (If known)

**Block 11. Supplementary Notes.** Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of ..., To be published in .... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

**Block 12a. Distribution/Availability Statement.** Denote public availability or limitation. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR)

**DOD** - See DoDD 5230.24, "Distribution Statements on Technical Documents."

**DOE** - See authorities

**NASA** - See Handbook NHB 2200.2.

**NTIS** - Leave blank.

### **Block 12b. Distribution Code.**

**DOD** - DOD - Leave blank

**DOE** - DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports

**NASA** - NASA - Leave blank

**NTIS** - NTIS - Leave blank.

**Block 13. Abstract.** Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

**Block 14. Subject Terms.** Keywords or phrases identifying major subjects in the report.

**Block 15. Number of Pages.** Enter the total number of pages.

**Block 16. Price Code.** Enter appropriate price code (NTIS only).

**Blocks 17. - 19. Security Classifications.** Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

**Block 20. Limitation of Abstract.** This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.